



THE SUBDIVISION OF SECTION 20,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T17S R1W  
C  
N 1/16 | S20  
C  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on a N slope in dense pinon and juniper.

**80.480** The 1/4 section corner of sections 17 and 20.

---

From the 1/4 section corner of sections 20 and 21.

S. 89°20.2' W., on the E - W center line section 20.

**19.880** Point for the center E 1/16 section corner of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone with aluminum cap marked:

T17S R1W  
C    E 1/16    C  
      S20  
      1993

The corner falls on top of spur ridge, slopes E in scattered pinon and juniper.

**39.760** The center 1/4 section corner.

**75.980** The 1/4 section corner of section 20 only.

---

From the center E 1/16 section corner of section 20.

N. 1°40.6' W., on the N -S center line of the NE 1/4 of section 20.

**20.006** Point for the NE 1/16 section corner, at intersection with the E - W center line of the NE 1/4 of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 20,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T17S R1W  
NE 1/16  
S20  
1993

The corner falls on a steep NW slope in sagebrush and scattered pinon and juniper.

40.000

The E 1/16 section corner of sections 17 and 20.

From the N 1/16 section corner of sections 20 and 21.

S. 88°57.6' W., on the E - W center line of the NE 1/4 of section 20.

20.010

The NE 1/16 section corner.

39.952

The center N 1/16 section corner.

The Subdivision of Section 21,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 21 and 28.

N. 1°40.8' W., on the N - S center line of section 21.

20.035

Point for the center S 1/16 section corner of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T17S R1W  
C  
S 1/16 | S21  
C  
1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, 3 ft. base by 2 ft. high NW of the corner.

The corner falls within a draw, drains SE in juniper growth.

40.070

Point for the center 1/4 section corner at intersection with the E - W center line of section 21.

THE SUBDIVISION OF SECTION 21,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with aluminum cap marked:

T17S R1W  
C 1/4  
S21  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gradual N slope, in sagebrush.

**60.118** Point for the center N 1/16 section corner of section 21, falls with Sevier Bridge Reservoir; not monumented.

**80.166** The 1/4 section corner of sections 16 and 21.

---

From the 1/4 section corner of sections 21 and 22.

S. 88°42.6' W., on the E - W center line of section 21.

**40.104** The center 1/4 section corner.

**60.182** Point for the center W 1/16 section corner of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone 4 ft. base, to top of aluminum cap marked:

T17S R1W  
C  $\frac{W \ 1/16}{S21}$  C  
1993

The corner falls on a NW slope in scattered pinon and juniper.

**80.260** The 1/4 section corner of sections 20 and 21.

---

From the W 1/16 section corner of sections 21 and 28.

N. 1°43.4' W., on the N - S center line of the SW 1/4 of section 21.

**20.052** Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:



THE SUBDIVISION OF SECTION 21,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T17S R1W  
SW 1/16  
S21  
1993

The corner falls in a hollow, bears E, on a gradual E slope in sagebrush and scattered juniper.

**40.104** The center W 1/16 section corner.

From the center S 1/16 section corner of section 21.

S.  $88^{\circ}39.6'$  W., on the E - W center line of the SW 1/4 of section 21.

**20.064** The SW 1/16 section corner.

**40.128** The S 1/16 section corner of sections 20 and 21.

From the center W 1/16 section corner of section 21.

N.  $1^{\circ}34.3'$  W., on the N - S center line of the NW 1/4 of section 21.

**20.092** Point for the NW 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 21, falls within the Sevier Bridge Reservoir; not monumented.

**40.172** Point for the W 1/16 section corner of sections 16 and 21.

From the point for the center N 1/16 section corner of section 21.

S.  $88^{\circ}50.2'$  W., on the E - W center line of the NW 1/4 of section 21.

**20.040** Point for the NW 1/16 section corner.

**40.014** The N 1/16 section corner of sections 20 and 21.

The Subdivision of Section 28,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 28 and 33.

N.  $1^{\circ}56.0'$  W., on the N - S center line of section 28.

THE SUBDIVISION OF SECTION 28,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.153

Point for the center 1/4 section corner at intersection with the E - W center line of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground in a collar of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located, 1.50 chs. N of a trail road in the bottom of a wash, drains E, in scattered pinon and juniper.

60.176

Point for the center N 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T17S R1W  
C  
N 1/16 | S28  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner falls on a gradual N slope in sagebrush.

80.199

The 1/4 section corner of sections 21 and 28.

From the point for the 1/4 section corner of sections 27 and 28.

S. 88°35.2' W., on the E - W center line of section 28.

20.143

Point for the center E 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone and with aluminum cap marked:

T17S R1W  
C E 1/16 C  
S28  
1993

THE SUBDIVISION OF SECTION 28,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner falls on a E slope in scattered pinon and juniper.

**40.286** The center 1/4 section corner of section 28.

**80.582** The 1/4 section corner of sections 28 and 29.

---

From the center E 1/16 section corner of section 28.

N. 1°58.3' W., on the N - S center line of the NE 1/4 of section 28.

**20.055** Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T17S R1W  
NE 1/16  
S28  
1993

The corner falls underneath power lines on a gradual E slope in sagebrush.

**40.110** The point for the E 1/16 section corner of sections 21 and 28.

---

From the point for the N 1/16 section corner of sections 27 and 28.

S. 88°30.0' W., on the E - W center line of the NE 1/4 of section 28.

**20.128** The NE 1/16 section corner.

**40.256** The center N 1/16 section corner.

---

From the E 1/16 section corner of sections 28 and 33.

N. 2°01.4' W., on the N - S center line of the SE 1/4 of section 28.

**40.158** The center E 1/16 section corner.

---

THE SUBDIVISION OF SECTION 33,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The Subdivision of Section 33,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 4 and 33, on the south boundary of the township; hereinafter described.

N. 2°11.3' W., on the N - S center line of section 33.

**39.232** Point for the center 1/4 section corner at intersection with the E - W center line of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground in a collar of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S33  
1993

Raise a mound of stone, 3 ft. base by 2 ft. high, W of the corner.

The corner falls on a E slope in pinon and juniper.

**79.456** The 1/4 section corner of sections 28 and 33.

From the 1/4 section corner of sections 33 and 34.

S.88°37.6' W., on the E - W center line of section 33.

**20.083** Point for the center E 1/16 section corner of section 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T17S R1W  
C E 1/16 C  
S33  
1993

The corner falls on a E slope in pinon and juniper.

**40.166** The center 1/4 section corner of section 28.

**81.079** The 1/4 section corner of sections 32 and 33.

THE SUBDIVISION OF SECTION 33,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the center E 1/16 section corner of section 33.

N. 2°00.5' W., on the N - S center line of the NE 1/4 of section 33.

40.230

The E 1/16 section corner of section 28 and 33.

---

The Subdivision of Section 35,  
T. 17 S., R. 1 W., Salt Lake Meridian, Utah

---

From the point for the 1/4 section corner of sections 2 and 35, on the south boundary of the township; hereinbefore described.

N. 1°31.2' W., on the N - S center line of section 35.

40.300

Point for the center 1/4 section corner at intersection with the E - W center line of section 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground in a collar of stone, with aluminum cap marked:

T17S R1W  
C 1/4  
S35  
1993

Set a steel fence post alongside the aluminum post.

The corner falls within plowed ground.

80.180

The 1/4 section corner of sections 26 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1973-74.

---

From the 1/4 section corner of sections 35 and 36.

S.88°13.5' W., on the E - W center line of section 35

19.927

Point for the center E 1/16 section corner of section 35.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 35,  
T. 17 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T17S R1W  
C E 1/16 C  
S35  
1993

The corner falls on a E slope in pinon and juniper.

**39.854** The center 1/4 section corner of section 35.

**79.654** The point for the 1/4 section corner of sections 34 and 35.

---

From the E 1/16 section corner of sections 2 and 35 on the south boundary of the township;  
hereinbefore described.

N. 1°23.3' W., on the N - S center line of the SE 1/4 of section 35.

**40.327** The center E 1/16 section corner of section 35.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

---

Name	Capacity
Gail E. Reynolds	Cadastral Surveyor

## CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *16th day of September, 1992*, I have *dependently resurveyed a portion of the north and south boundaries, a portion of the subdivisional lines and subdivided sections 4, 5, 8, 9, 17, 20, 21, 28, 33, and 35, in Township 17 South, Range 1 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

\_\_\_\_\_  
April 22, 1997

Date

\_\_\_\_\_  
*Ferrel D. Reynolds*

(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the north and south boundaries, a portion of subdivisional lines and subdivided sections 4, 5, 8, 9, 17, 20, 21, 28, 33 and 35, in Township 17 South, Range 1 West, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

\_\_\_\_\_  
April 24, 1997

Date

\_\_\_\_\_  
*Daniel W. Webb*

(Chief Cadastral Surveyor for Utah)



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE DEPENDENT RESURVEY

OF

PORTIONS OF THE WEST BOUNDARY

AND SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF CERTAIN SECTIONS

IN

TOWNSHIP 41 SOUTH, RANGE 11 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Larry V. Judd*  
*Cadastral Surveyor*

Under special instructions dated *October 26, 1992*, approved October 27, 1992, which provided for the surveys included under Group Number 793, and assignment instructions dated *November 4, 1992*.

Survey commenced *November 4, 1992*

Survey completed *November 5, 1993*

## INDEX DIAGRAM

Township 41 South , Range 11 West

6	5	4	3	2	1
7	8	9	10	11	12
4 13	11 12	7			
4 18	11 17	7 16	15	14	13
3 10	9 9	6 7			
2 19	8 20	5 21	22	23	24
2 8		5			
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 17.....Page 14

The Subdivision of Section 18.....Page 16

The Subdivision of Section 19.....Page 20

The Subdivision of Section 20.....Page 22

## TOWNSHIP 41 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of portions of the west boundary and subdivisional lines and the subdivision of sections 17, 18, 19, and 20, in Township 41 South, Range 11 West, Salt Lake Meridian, Utah.

**History of Surveys****Surveyed by****Retr. or Resurveyed by****NORTH BOUNDARY**

Portion	Bailey and Burrill	1877		
Portion	A.D. Ferron	1877		
Portion	Collier and Gentry	1909	Collier and Gentry	1909
Portion			Nelson and Stumm	1911
Portion	J.W. Dougall	1916	J.W. Dougall	1916
Portion			G.V. Olson	1970
Portion			R.A. Zaninovich	1988

**SOUTH BOUNDARY**

All	J.G. Burrill	1877		
All	Collier and Gentry	1909	Collier and Gentry	1909-10
Portion			R.A. Zaninovich	1983

**EAST BOUNDARY**

Portion	Collier and Gentry	1909		
---------	--------------------	------	--	--

**WEST BOUNDARY**

Portion	J.G. Burrill	1877		
All	Collier and Gentry	1909	Collier and Gentry	1909
Portion			D.A. Buhler	1983
Portion			R.A. Zaninovich	1983

**SUBDIVISION**

Portion	Bailey and Burrill	1877		
Portion	Collier and Gentry	1909	Collier and Gentry	1909-10
Portion	G.V. Olson	1970		
Portion			R.A. Zaninovich	1983

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 793, Utah, dated October 26, 1992.

The directions of lines were determined by references to true meridians established on line by hour angle observations on Polaris. The lines were carried forward by sustained angulations, being supplemented by other observations taken throughout the progress of the survey. Distances were determined by electronic measurement.

## TOWNSHIP 41 SOUTH, RANGE 11 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 20, 21, 28, and 29, as determined by a tie made to U.S. Geological Survey triangulation station "CRATER HILL ( BESS )" is as follows:

Latitude 37° 11' 59.40" N.    Longitude 113° 06' 31.17" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey "Magnetic Declination Map of 1990" is: 13 1/2° East.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 41 S., R. 11 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
Collier and Gentry, Deputy Surveyors in 1909

---

Beginning at the corner of sections 19, 24, 25, and 30, T. 41 S., Rs. 11 and 12 W., monumented with an iron post, 3 ins. diam., firmly set, in a mound of stone, with brass cap, marked as described in the official record of the 1909 resurvey.

N. 0° 01' E., along the west boundary of section 19.

Over rolling open desert land.

**19.955** Point for the S 1/16 section corner of section 19 only, not monumented.

**26.10** Dalton Wash road, dirt, 15 lks. wide, course NE and SW.

Begin ascend on southerly slope.

**39.91** The 1/4 section corner of section 19 only, monumented with an iron post, 1 inch diam., firmly set, projecting 8 ins. above ground, with brass cap, marked 1/4 S19 S24 1909. I remove the marks on the cap, pertaining to section 24.

Raise a mound of stone 2 ft. base, 2 ft. high, E of the corner.

---

N. 0°07' E., beginning new measurement.

**0.805** Point for the 1/4 section corner of section 24 only; T. 41 S., R. 12 W.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base to top of aluminum cap marked:

T41S  
R12W R11W  
1/4 |  
S24 |  
1992

**31.75** Top of steep ascend, thence on gradual ascend.

**40.03** The corner of sections 18 and 19, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the 1909 survey.

From which the original bearing trees

A cedar, 18 ins. diam., bears S. 76° W., 211 lks. dist., marked  
T41S R11W S19 BT (record, pine 12 ins. diam., S. 80° E., 98 lks. dist.).

A cedar, 30 ins. diam., bears S. 80°30' W., 1.59 chs. dist., marked  
T41S R12W S13 BT (record, N. 80°30' W., 1.58 chs. dist.).

---

N. 0°01.5' W., along the west boundary of section 18.

On gradual easterly slope, in scattered pinon and juniper.

**1.495** The closing corner of sections 13 and 24, T. 41 S., R. 12 W., monumented with an iron post, 2 ins. diam., firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1909 survey.

There is no remaining evidence of the original bearing tree.

**19.97** Point for the S 1/16 section corner of section 18 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base to top of aluminum cap marked:

T41S  
R12W R11W  
| S 1/16  
| S18  
1992

Corner is set on gradual E slope in scattered pinon and juniper.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

CHAINS  
39.94

The 1/4 section corner of section 18 only, monumented with an iron post, 1 inch diam., firmly set in a mound of stone, with brass cap marked 1/4 S13 S18.  
I remove the marks on the cap pertaining to section 13.

N. 0°02.5' E., beginning new measurement.

2.00

Point for the E 1/4 section corner of section 13 only, T. 41 S., R. 12 W.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T41S  
R12W R11W  
1/4 |  
S13 |  
1992

Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W of corner.

Corner falls on open moderate E slope in grass clearing.

20.02

The N 1/16 section corner of section 18 only, monumented with a rebar 5/8 inch diam., firmly set, with 1 inch diam., plastic cap marked Ken Hamblin RLS 6687; this monument is accepted as a careful and faithful establishment of the corner point.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T41S  
R12W R11W  
| N 1/16  
| S 18  
1992

Raise a mound of stone 4 ft. base, 2 ft. high, E of the corner.

Deposit the rebar inside the aluminum post.

40.04

The corner of sections 7 and 18, monumented with an iron post, 3 ins. diam., firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1909 survey.

From this corner, U.S. Geological Survey Triangulation Station "VIRGIN", bears N. 63° 47.3' W., 228.210 chs. distance.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From this same corner, the closing corner of sections 12 and 13, T. 41 S., R. 12 W., monumented with an iron post, 2 ins. diam., set marked and witnessed as described in the official record of the 1909 survey, bears N. 0° 04' E., 1.96 chs. distance.

---

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 41 S., R. 11 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by  
Collier and Gentry, Deputy Surveyors in 1909

---

From the corner of sections 20, 21, 28, and 29, monumented with an iron post, 2 ins. diam., firmly set, projecting 24 ins. above ground, with brass cap marked as described in the official record of the 1909 survey. Raise a mound of stone around the iron post, 4 ft. base, 2 ft. high.

From which the original bearing trees

A cedar, 15 ins. diam., bears N. 59° E., 1.15 chs. dist., with scribe marks visible on open blaze.

A pine, 25 ins. diam., bears S. 42°45' E., 1.08 chs. dist., with scribe marks visible on open blaze.

A cedar, 25 ins. diam., bears S. 29°50' W., 55 lks. dist., with scribe marks visible on open blaze.

A cedar, 13 ins. diam., bears N. 68°15' W., 1.15 chs. dist., with scribe marks visible on open blaze.

From this corner U.S. Geological Survey triangulation station "CRATER HILL ( BESS )" bears N. 24°33.7' E., 62.640 chs. dist., monumented with an iron post, 1 inch diam., projecting 2 ins. above the ground with no cap.

N. 0°03' W., between sections 20 and 21.

Over broken sandstone outcroppings, on rolling mesa.

39.93

The 1/4 section corner of sections 20 and 21, monumented with an iron post 1 inch diam., firmly set, projecting 16 ins. above ground, with brass cap marked as described in the official record of the 1909 survey. Raise a mound of stone around the iron post, 3 ft. base 2 ft. high.

From which the original bearing trees.

A cedar, 8 ins. diam., bears S. 5° W., 32 lks. dist., with scribe marks 1/4 S20 BT, visible on open blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

There is no remaining evidence of the other original bearing tree.

N. 0°06' W., beginning new measurement.

19.98

Point for the N 1/16 section corner of sections 20 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

N 1/16	
S20	S21
1992	

Set a 7 ft. long steel fence post alongside the corner.

From the corner the corner of a 4 strand barbwire fence, projecting N and W, bears S. 87°W., 23 lks. dist.

39.96

Point for the corner of sections 16, 17, 20, and 21, at proportionate distance. There is no remaining evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T41S R11W	
S17	S16
S20	S21
1992	

Corner falls 23 lks. E., of a 4 strand barbwire fence, projecting N and S, and 30 lks. E of dirt road, 15 lks. wide, course N and S.

From this corner, the 1/4 section corner of sections 17 and 20, bears S. 89°53' W., 40.00 chs. distance, hereinafter described.

From the 1/4 section corner of sections 16 and 21, as determined from the original bearing trees. There was no remaining evidence of the original iron post.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T41S R11W

$$1/4 \frac{S16}{S21}$$

1992

from which the original bearing trees.

A cedar, 14 ins. diam., bears S. 26° E., 47 lks. dist., with faint scribe marks visible through partly healed blaze.

A cedar, stump 7 ins. diam., bears N. 39° 30' W., 44 lks. dist., with no remaining scribe marks visible.

Raise a mound of stone 3 ft. base, 2 ft. high, N of the corner

N. 89°56.5' W., bet. sections 16 and 21.

39.90

The corner of sections 16, 17, 20, and 21.

N. 0° 02' W., between sections 16 and 17.

Over rolling mesa in scattered pinon and juniper.

39.96

The 1/4 section corner of sections 16 and 17, monumented with an iron post, 1 inch diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1909 survey.

Corner is located 1 lk. west of the corner of a 4 strand barbwire fence, projecting N. and E.

N. 0°03' W., beginning new measurement.

39.995

The corner of sections 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap marked as described in the official record of the 1909 survey.

Corner is located at the corner of a 4 strand barbwire fence, projecting N, S, and W.

Raise a mound of stone 3 ft. base, 2 ft. high, E of the corner.

Reestablishment of the Survey Executed by  
Collier and Gentry, Deputy Surveyors in 1909  
and the Resurvey by R. Zaninovich in 1983

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 section corner of sections 19 and 30, monumented with an iron post, 1 inch diam., firmly set, in a mound of stone, with brass cap marked as described in the official record of the 1909 survey.

S. 89°57' W., between sections 19 and 30.

Over open rolling land.

**20.015** Point for the W 1/16 section corner of sections 19 and 30; not monumented.

**39.96** The corner of sections 19, 24, 25, and 30, T. 41 S., R. 11 and 12 W., hereinbefore described.

From the corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the 1909 survey.

Corner is located west, 95 lks. dist., from a wash 15 lks. wide, course N. 56° W., and E., and 30 lks. dist., from a wash 20 lks. wide, course N. 25° W.

N. 0°06' W., between sections 19 and 20.

Over rolling open land.

**20.015** Point for the S 1/16 section corner of sections 19 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

S 1/16  
S19 | S20  
1992

Raise a mound of stone 3 ft. base, 1 ft. high, W of the corner.

**20.30** South edge of a wash 12 lks. wide, 8 ft. deep, course S. 70° W.

**40.03** The 1/4 section corner of sections 19 and 20, monumented with an iron post, rusted through and in 2 pieces, with the bottom portion firmly set, in the ground, and the top portion with brass cap, lying loose on top of the ground, with brass cap marked as described in the official record of the 1909 survey.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T41S R11W

1/4

S19 | S20

1992

Raise a mound of stone 3 ft. base, 3 ft. high, N of the corner.

Deposit the original iron post inside the aluminum post.

Corner falls in a east and west fence line, 10 lks. E of a wash, 10 lks. wide, 4 ft. deep, course SW.

N. 0°01.5' W., beginning new measurement.

4.00 Begin ascend on broken westerly slope.

19.93 Point for the N 1/16 section corner of sections 19, and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone 4 ft. base to top of aluminum cap marked:

N 1/16

S19 | S20

1992

The corner is located on a steep westerly slope.

39.86 The corner of sections 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., loosely set, projecting 32 ins. above ground, with brass cap marked as described in the official record of the 1909 survey.

At the corner point, reset the original iron post to project 16 ins. above ground, in a mound of stone 3 ft. base, to top of brass cap.

This corner falls on a steep westerly slope.

From the 1/4 section corner of sections 17 and 20, monumented with an iron post, 1 inch diam., firmly set, projecting 16 ins. above ground, with brass cap marked as described in the official record of the 1909 survey.

from which the original bearing trees

A cedar, 24 ins. diam., bears N. 16°15' E., 104 lks. dist., ( record 103 lks.), with scribe marks visible, through partly healed blaze.

A cedar, 18 ins. diam., bears S. 70°50' W., 48 lks. dist., with scribe marks visible, on open blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Raise a mound of stone around the iron post, 3 ft. base to top of brass cap.

S. 89°55' W., between sections 17 and 20.

19.98

Point for the W 1/16 section corner of sections 17 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock and in a mound of stone, 4 1/2 ft. base, 2 1/2 ft. high, with aluminum cap marked:

W 1/16  $\frac{S17}{S20}$   
1992

20.34

A 4 strand barbwire fence, projecting N and S.

34.20

Edge of mesa, bears N and S.

39.96

The corner of sections 17, 18, 19 and 20.

S. 89°56' W., between sections 18 and 19.

Over open desert land.

19.97

Point for the E 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

E 1/16  $\frac{S18}{S19}$   
1992

Raise a mound of stone 3 ft. base, 2 ft. high, N. of the corner.

Corner is located in a low flood plane area.

23.15

Dalton wash road, dirt, 15 lks. wide, bears N and S.

39.94

The 1/4 section corner of sections 18 and 19, monumented with an iron post, 1 inch diam., firmly set, projecting 8 ins. above ground, with a steel fence post alongside, with brass cap marked as described in the official record of the 1909 survey.

Corner is located 3 lks. west of the west edge of a dirt road, 15 lks. wide which bears N and S.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

West, beginning new measurement.

**19.95** Point for the W 1/16 section corner of sections 18 and 19, not monumented.

**39.76** The corner of sections 18 and 19, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 17, 18, 19, and 20.

N. 0°03' W., between sections 17 and 18.

Along broken westerly slope.

**19.98** Point for the S 1/16 section corner of sections 17 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

S 1/16  
S18 | S17  
1992

Raise a mound of stone, 5 ft. base, 4 ft. high, W. of the corner.

The corner is located on a steep W descending slope.

**39.96** The 1/4 section corner of sections 17 and 18, monumented with an iron post, 1 inch diam., firmly set, projecting 16 ins. above ground, with brass cap marked as described in the official record of the 1909 survey.

Raise a mound of stone 4 ft. base, 1 ft. high around the iron post.

---

N. 0°02' W., beginning new measurement.

**5.35** Dalton wash road, dirt, 15 lks. wide, bears N. 21° E. and S. 21° W.

**20.02** Point for the N 1/16 section corner of sections 17 and 18, not monumented.

**40.04** The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 ins. diam., loosely set, in a mound of stone, with brass cap marked as described in the official record of the 1909 survey.

from which the original bearing trees

A cedar, 14 ins. diam., bears N. 76°45' E., 55 lks. dist., with faint scribe marks visible, on rotted out blaze.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

A cedar, 24 ins. diam., bears N. 25°45' W., 81 lks. dist., with scribe marks  
S7 B visible, on dead fork of tree.

There is no remaining evidence of the other record bearing trees.

Corner falls in a barbwire fence, projecting E. and W.

Raise a mound of stone around the iron post, 4 ft. base, 2 1/2 ft. high.

---

From the corner of sections 8, 9, 16, and 17.

S. 89°57' W., between sections 8 and 17.

Over rolling mesa.

39.98

The 1/4 section corner of sections 8 and 17, monumented with an iron post 1 inch diam., set in a mound of stone, with the upper portion of the iron post rusted through and missing, no brass cap found.

At the corner point

Set a rebar 14 ins. long 3/4 inch diam., drilled 10 ins. into solid sandstone, with 2 1/2 inch diam., aluminum cap marked:

T41S R11W  
1/4  $\frac{S8}{S17}$   
1992

Raise a mound of stone 3 ft. base, 1 ft. high, N of the corner.

---

S. 89°54.5' W., beginning new measurement

19.985

Point for the W 1/16 section corner of sections 8 and 17, not monumented.

38.00

Edge of mesa bears NE and SW.

39.97

The corner of sections 7, 8, 17, and 18.

---

From the 1/4 section corner of sections 7 and 18, monumented with a rebar, 5/8 inch diam., firmly set, projecting 5 ins. above ground, in a mound of stone, with 1 inch diam., plastic cap marked Ken Hamblin RLS 6687, and a portion of the original iron post also found within the mound; this monument is accepted as a careful and faithful reestablishment of the corner point.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T41S R11W  
1/4  $\frac{S7}{S18}$   
1992

from which the original bearing trees

A cedar, 12 ins. diam., bears N. 31°15' E., 67 lks. dist., with scribe marks  
1/4 S7 BT visible, through partly healed blaze.

A cedar, 15 ins. diam., bears S. 63° E., 65 lks. dist., with scribe marks  
1/4 S18 BT visible, on open blaze.

Raise a mound of stone 2 ft. base, 2 ft. high, N. of the corner.

Bury the rebar and iron post alongside the aluminum post.

Corner is located within a cultivated area.

S. 89°57' W., between sections 7 and 18.

Over rolling mesa in scattered pinon and juniper.

**19.945** Point for the W 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

W 1/16  $\frac{S7}{S18}$   
1992

Raise a mound of stone 3 ft. base, 2 ft. high, N of the corner.

From the corner a rebar, 5/8 inch diam., firmly set, projecting 8 ins. above ground, 1 inch diam., with plastic cap marked Ken Hamblin RLS 6687, bears N. 87° W., 12.3 lks. dist.

**39.65** The corner of sections 7 and 18, on the west boundary of the township, hereinbefore described.

---

THE SUBDIVISION OF SECTION 17,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The Subdivision of Section 17,  
T. 41 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 17 and 20.

N. 0°02' W., on the N - S center line of section 17.

**19.985** Point for the center S 1/16 section corner of sec. 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

C  
S 1/16 | S17  
C  
1992

Raise a mound of stone 3 ft. base, 1 ft. high, W of the corner.

**39.97** Point for the center 1/4 section corner, at intersection with the E - W center line of sec. 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base to top of aluminum cap marked:

T41S R11W  
C 1/4  
S17  
1992

Corner falls in a 4 strand barbwire fence, projecting E and W.

**59.00** Edge of mesa bears N. 30° E., and S. 30° W.

**59.99** Point for the center N 1/16 section corner of sec. 17.

Set a rebar, 8 ins. long 5/8 inch diam., drilled 7 ins. into solid sandstone, with 2 1/2 inch diam., aluminum cap marked:

C  
N 1/16 | S17  
C  
1992

Raise a mound of stone 2 ft. base, 2 ft. high, NW of the corner.

Corner falls underneath a rock overhang.



THE SUBDIVISION OF SECTION 17,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From this corner, a rebar 5/8 inch diam., with 1 inch diam., plastic cap marked Ken Hamblin RLS 6687, was found lying loose near the corner point, and therefore was not utilized as the corner position.

80.01

The 1/4 section corner of sections 8 and 17.

---

From the 1/4 section corner of sections 16 and 17.

S. 89°54' W., on the E - W center line of section 17.

40.00

The center 1/4 section corner of section 17.

59.985

Point for the center W 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

C —  $\frac{W \ 1/16}{S17}$  — C  
1992

Raise a mound of stone 3 ft. base, 1 1/2 ft. high, N of the corner.

68.45

Edge of mesa, bears north and south.

79.97

The 1/4 section corner of sections 17 and 18.

---

From the W 1/16 section corner of sections 17 and 20.

N. 0°02.5' W., on the N - S center line of the SW 1/4 of section 17.

19.98

Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap marked:

SW 1/16  
S17  
1992

Raise a mound of stone 4 ft. base, 1 1/2 ft. high, N of the corner.

From this corner, the corner of a 4 strand barbwire fence projecting S and E, bears N. 70° E., 42 lks. dist.

THE SUBDIVISION OF SECTION 17,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.96

The center W 1/16 section corner.

---

From the center S 1/16 section corner of section 17.

S. 89°54.5' W., on the E - W center line of the southwest 1/4 of section 17.

19.985

The SW 1/16 section corner of section 17.

39.97

The S 1/16 section corner of sections 17 and 18.

---

From the center W 1/16 section corner of section 17.

N. 0°02' W., on the N - S center line of the northwest 1/4 of section 17.

20.02

Point for the NW 1/16 section corner, at intersection with the E - W center line of the northwest 1/4 of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone 4 ft. base to top of aluminum cap marked:

NW 1/16  
S17  
1992

Corner falls at the base of a rock outcrop 20 ft. high.

40.04

Point for the west 1/16 section corner of sections 8 and 17.

---

From the center north 1/16 section corner of section 17.

S. 89°54' W., on the E - W center line of the northwest 1/4 of section 17.

19.985

The NW 1/16 section corner of section 17.

39.97

The N 1/16 section corner of sections 17 and 18.

---

The Subdivision of Section 18,  
T. 41 S., R. 11 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 18 and 19.

N. 0°04' W., on the N - S center line of section 18.

THE SUBDIVISION OF SECTION 18,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

19.985

Point for the center S 1/16 corner of section 18, not monumented.

39.97

Point for the center 1/4 section corner at intersection with the E - W center line of section 18, monumented with a bent rebar 5/8 inch diam., firmly set, with 1 inch diam., plastic cap marked Ken Hamblin RLS 6687. This corner is accepted as a faithful determination of the position of the corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T41S R11W  
C 1/4  
S18  
1992

Raise a mound of stone 2 1/2 ft. base, 2 ft. high, W of the corner.

Deposit the rebar alongside the aluminum post.

52.00

Edge of mesa, bears east and west.

59.995

Point for the center N 1/16 section corner of section 18, not monumented.

80.02

The 1/4 section corner of sections 7 and 18.

From the 1/4 section corner of sections 17 and 18.

S. 89°57.5' W., on the E - W center line of section 18.

19.975

Point for the center E 1/16 section corner of section 18, not monumented.

39.95

The center 1/4 section corner of section 18.

59.91

Point for the center W 1/16 section corner of section 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C  $\frac{W \ 1/16}{S18}$  C  
1992

Raise a mound of stone 3 ft. base, 2 ft. high, E of the corner.

Corner falls 14 lks. west from the edge of the mesa rim.

THE SUBDIVISION OF SECTION 18,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From this corner, a rebar 5/8 inch diam., firmly set, projecting 2 ins. above ground, with 1 inch diam., with plastic cap, marked Ken Hamblin RLS 6687, bears N. 88° W., 9 lks. dist.

79.68

The 1/4 section corner of section 18 only, on the west boundary of the township, hereinbefore described.

---

From the E 1/16 section corner of sections 18 and 19.

N. 0°03.5' W., on the N - S center line of the southeast 1/4 of section 18.

19.985

Point for the SE 1/16 section corner, at intersection with the E - W center line of the southeast 1/4 of section 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap marked:

SE 1/16  
S18  
1992

Raise a mound of stone N of the corner, and set a 6 ft. steel fence post, 2 ft. north of the aluminum post.

39.97

Point for the center E 1/16 section corner of section 18.

---

From the S 1/16 section corner of sections 17 and 18.

S. 89°57' W., on the E - W center line of the southeast 1/4 of section 18.

19.975

The SE 1/16 section corner of section 18.

39.95

Point for the center S 1/16 section corner of section 18.

---

From the point for the W 1/16 section corner of sections 18 and 19.

N. 0°05' W., on the N - S center line of the southwest 1/4 of section 18.

19.98

Point for the SW 1/16 section corner, at intersection with the E - W center line of the southwest 1/4 of section 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid bedrock, in a mound of stone, 5 ft. base to top of aluminum cap marked:

THE SUBDIVISION OF SECTION 18,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

SW 1/16  
S18  
1992

Corner falls on a steep southeasterly slope.

39.96

The center W 1/16 section corner of section 18.

---

From the point for the center S 1/16 section corner of section 18.

S. 89°59' W., on the E - W center line of the southwest 1/4 of section 18.

19.955

The SW 1/16 section corner of section 18.

39.74

The S 1/16 section corner of section 18 only, on the west boundary of the township, hereinbefore described.

---

From the center W 1/16 section corner of section 18.

N. 0°03' W., on the N - S center line of the northwest 1/4 of section 18.

20.025

Point for the NW 1/16 section corner, at intersection with the E - W center line of the northwest 1/4 of section 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone 4 ft. base to top of aluminum cap marked:

NW 1/16  
S18  
1992

From this corner, a rebar 5/8 inch diam., firmly set, projecting 12 ins. above ground, 1 inch diam., with plastic cap, marked Ken Hamblin RLS 6687, bears N. 87° W., 11 lks. dist.

40.05

The W 1/16 section corner of sections 7 and 18.

---

From the point for the center N 1/16 section corner of section 18.

S. 89°57' W., on the E - W center line of the northwest 1/4 of section 18.

19.95

The NW 1/16 section corner of section 18.

39.69

The N 1/16 section corner of section 18 only, on the west boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 19,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 19,  
T. 41 S., R. 11 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 19 and 30

N. 0°04.5' W., on the N - S center line of section 19.

19.99

Point for the center S 1/16 section corner of section 19.

Set a rebar 18 ins. long 5/8 inch diam., drilled 18 ins. into solid sandstone, with 2 1/2 inch diam., aluminum cap marked:

C  
S 1/16 | S19  
C  
1992

Raise a mound of stone 2 ft. base, 1 1/2 ft. high, W of the corner.

From this corner the corner of fences, projecting N and W, bears N. 60° W., 15 lks. dist.

39.98

Point for the center 1/4 section corner, at intersection with the E - W center line of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T41S R11W  
C 1/4  
S19  
1992

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the corner.

From this corner, the corner of fences, projecting N, S, and E, bears S. 25° W., 10 lks. dist.

59.94

Point for the center N 1/16 section corner of section 19; not monumented.

79.90

The 1/4 section corner of sections 18 and 19.

From the 1/4 section corner of sections 19 and 20.

S. 89°51' W., on the E - W center line of section 19.

THE SUBDIVISION OF SECTION 19,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****19.955**

Point for the center E 1/16 section corner of section 19, not monumented.

**39.91**

The center 1/4 section corner of section 19.

**58.75**

Dirt road, 15 lks. wide bears NE and SW.

**59.91**

Point for the center W 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

C —  $\frac{W \ 1/16}{S19}$  — C  
1992

Raise a mound of stone, 4 ft. base, 2 ft. high, N of the corner.

**79.80**

The 1/4 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

---

From the point for the center E 1/16 section corner of section 19.

N. 0°03' W., on the N - S center line of the northeast 1/4 of section 19.

**19.945**

Point for the NE 1/16 section corner at intersection with the E - W center line of the northeast 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

NE 1/16  
S19  
1992

From this corner, the corner of fences projecting S and E, bears S. 45° W., 1.5 lks. dist.

**39.89**

The east 1/16 section corner of sections 18 and 19.

---

From the N 1/16 section corner of sections 19 and 20.

S. 89°53.5' W., on the E - W center line of the northeast 1/4 of section 19.

**19.965**

The NE 1/16 section corner of section 19.

**39.93**

Point for the center N 1/16 section corner of section 19.

THE SUBDIVISION OF SECTION 19,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the point for the W 1/16 section corner of sections 19 and 30.

N. 0°03.5' W., on the N - S center line of the southwest 1/4 of section 19.

19.975

Point for the SW 1/16 section corner at intersection with the E - W center line of the southwest 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

SW 1/16  
S19  
1992

Raise a mound of stone 3 ft. base, 2 ft. high, N of the corner.

20.085

Fence, projecting E and W.

39.95

The center W 1/16 section corner of section 19.

---

From the center S 1/16 corner of section 19.

S. 89°54' W., on the E - W centerline of the SW 1/4 of section 19.

20.01

The SW 1/16 section corner of section 19.

39.93

The S 1/16 section corner of section 19 only, on the west boundary of the township hereinbefore described.

---

The Subdivision of Section 20  
T. 41 S., R. 11 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 20 and 29, monumented with an iron post, 1 inch diam., firmly set in a mound of stone with brass cap marked as described in the official record of the 1909 survey.

The corner falls 5 lks. S. Of a small ledge, and 1 lk. N. of a cedar post, 6 ins. diam., set in a mound of stone.

N. 0°04' W., on the N - S center line of section 20.

9.20

Top edge of mesa, bears SE and NW.



THE SUBDIVISION OF SECTION 20,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

CHAINS  
20.00

Point for the center S 1/16 section corner of section 20.

Set an aluminum post 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top of aluminum cap marked:

C  
S 1/16 | S20  
C  
1992

40.00

Point for the center 1/4 section corner, at intersection with the E - W center line of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, in a mound of stone, 5 ft. base to top of aluminum cap marked:

T41S R11W  
C 1/4  
S20  
1992

59.95

Point for the center N 1/16 section corner of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

C  
N 1/16 | S20  
C  
1992

Corner falls in a 4 strand barbwire fence, projecting E and W. The corner of the E and W fence and a fence projecting N. 20° W., bears E 11 lks. dist.

79.90

The 1/4 section corner of sections 17 and 20.

---

From the 1/4 section corner of sections 20 and 21.

S. 89°58' W., on the E - W center line of section 20.

40.02

The center 1/4 section corner of section 20.

60.02

Point for the center W 1/16 section corner of section 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 20,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

C  $\frac{W \ 1/16}{S20}$  C  
1992

Raise a mound of stone, 3 ft. base, 2 ft. high, N of the corner.

**63.30** Edge of mesa, bears NW and SE.

**80.02** The 1/4 section corner of sections 19 and 20.

From the N 1/16 section corner of sections 20 and 21.

S. 89°55.5' W., on the E - W center line of the northeast 1/4 of section 20.

**40.01** The center N 1/16 section corner of section 20.

From the center S 1/16 section corner of section 20.

S. 89°57' W., on the E - W center line of the southwest 1/4 of section 20.

**39.99** The S 1/16 section corner of sections 19 and 20.

From the center W 1/16 section corner of section 20.

N. 0°03' W., on the N - S center line of the northwest 1/4 of section 20.

**19.94** Point for the NW 1/16 section corner, at intersection with the E - W center line of the northwest 1/4 of section 20.

Set a rebar 18 ins. long 3/4 inch diam., drilled 12 ins. into solid sandstone, with 2 1/2 inch diam., aluminum cap marked:

NW 1/16  
S20  
1992

Raise a mound of stone 3 ft. base, 2 ft. high, N of the corner.

From this corner, the corner of a 4 strand barbwire fence, projecting N and E, bears N. 70° E., 16 lks. dist.

**39.88** The W 1/16 section corner of sections 17 and 20.

THE SUBDIVISION OF SECTION 20,  
T. 41 S., R. 11 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center N 1/16 section corner of section 20.

S. 89°56.5' W., on the E - W center line of the northwest 1/4 of section 20.

**19.99**

The NW 1/16 section corner of section 20.

**39.98**

The N 1/16 section corner of sections 19 and 20.

---

General Description

This area surveyed and resurveyed in sections 17, 18, 19, and 20, of T., 41 S., R. 11 W., is located approximately 3 miles northeasterly of the town of Virgin, Utah. The elevation varies from 4000 ft. along the Dalton wash to 4800 ft. on the mesa.

The terrain varies from cultivated fields and open desert to rolling bench areas of the mesa vegetated with pinon and juniper.

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Ronald K. Baugh	Land Surveyor
Shawn L. Peterson	Survey Technician
Joseph M. Dhaenens	Survey Technician
Steve Oatman	Survey Aid
Shane Button	Survey Aid


## CERTIFICATE OF SURVEY

I, **Larry V. Judd, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *26th day of October, 1992*, I have *dependently resurveyed portions of the west boundary and subdivisional lines and subdivided certain sections in Township 41 South, Range 11 West*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 22, 1997

Date

  
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of portions of the west boundary and subdivisional lines and subdivided certain sections in Township 41 South, Range 11 West, Salt Lake Meridian, Utah*,

executed by **Larry V. Judd, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

April 24, 1997

Date

  
(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF

THE RETRACEMENT OF A PORTION OF

THE WEST BOUNDARY

THE DEPENDENT RESURVEY

OF PORTIONS

OF THE SOUTH BOUNDARY

AND SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 19, 30, AND 31,

TOWNSHIP 16 SOUTH, RANGE 1 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds,  
Cadastral Surveyor*

Under special instructions dated *March 1, 1993*, approved *April 24, 1995*, which provided for the surveys included under Group Number 795, and assignment instructions dated *April 25, 1995*.

Survey commenced *June 1, 1995*

Survey completed *August 1, 1995*

# INDEX DIAGRAM

Township 16 South , Range 1 West

	6	5	4	3	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
4	13 12	11				
4	19	11 20	21	22	23	24
3	10 9	9				
3	30	9 29	28	27	26	25
3	8 7	7				
3	31	6 32	18 33	16 34	15 35	13 36
2	6 5	4				

The Subdivision of Section 19 .....	Page 13
The Subdivision of Section 30 .....	Page 19
The Subdivision of Section 31 .....	Page 26

## TOWNSHIP 16 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the retracement of a portion of the west boundary, the dependent resurvey of portions of the south boundary, and subdivisional lines, and the subdivision of sections 19, 30 and 31, in Township 16 South, Range 1 West, Salt Lake Meridian, Utah.

**History of Earlier Surveys****Surveyed by****Retr. or Resurveyed by****NORTH BOUNDARY (Third Standard Parallel South)**

Portion	C. Mogo	1856		
Portion	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			G.B. Hatch	1973

**SOUTH BOUNDARY**

Portion	C. Mogo	1856		
All	Stewart & Stewart	1898	Stewart & Stewart	1898
All			G.B. Hatch	1973

**EAST BOUNDARY ( Salt Lake Meridian )**

Portion	C. Mogo	1856		
All	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			G.B. Hatch	1973

**WEST BOUNDARY**

All	F. Dickert	1871		
All			G.B. Hatch	1973
Portion			F.D. Reynolds	1991

**SUBDIVISION**

All	F. Dickert	1871		
All	Stewart & Stewart	1898	Stewart & Stewart	1898
Portion			G.B. Hatch	1973

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 795, dated March 1, 1993.

The directions of the lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.



## TOWNSHIP 16 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey the lines of the original survey and resurveys were retraced and a diligent search was made for any evidence of the original and resurvey field note records. Identified corners, when appropriate were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original or resurvey record.

The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 5, 6, 31, and 32, T. 16 and 17 S., R. 1 W., as determined by a tie made to National Geodetic Survey Triangulation Station "YUBA" is as follows:

Latitude 39° 21'58.21" N.      Longitude 111° 57'28.86" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990 is 13 1/2° E.

---

Retracement of a Portion of the West Boundary,  
T. 16 S., R. 1 W., Salt Lake Meridian, Utah.

---



---

Reestablishment of the Survey Executed by F. Dickert in 1898  
and Resurveys Executed by G.B. Hatch in 1973  
and F.D. Reynolds in 1991

---

Beginning at the closing corner of sections 6 and 31, T. 17 S. and T. 16 S., R. 1 W., on the west boundary of the township, monumented with an iron post, 2 1/2 ins. diam., extending 6 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch.

From this corner

The 1/4 section corner of section 1 only, T. 17 S., R. 2 W., monumented with an iron post, 2 1/2 ins. diam., set 6 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch, bears S. 0°16.3' W., 2.270 chains distance.

N. 0°16.3' E., on the east boundary of section 1, T. 17 S., R. 2 W.

**19.9875** Point for the S 1/16 section corner of section 31 only, falls in Sevier Bridge Reservoir; not monumented.

**37.848** Point for the corner of sections 1 and 36, T. 16 and 17 S., R. 2 W. falls in Sevier Bridge Reservoir; not monumented.

---

RETRACEMENT OF A PORTION OF THE WEST BOUNDARY,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 0°16.3' E., on the east boundary of section 36, T. 16 S., R. 2 W.

**2.127** Point for the 1/4 section corner of section 31 only, falls in Sevier Bridge Reservoir; not monumented.

**22.1135** Point for the N 1/16 section corner of section 31 only, falls in Sevier Bridge Reservoir; not monumented.

**40.098** Point for the 1/4 section corner of section 36 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.

**42.100** Point for the closing corner of sections 30 and 31, falls in Sevier Bridge Reservoir; not monumented.

**62.109** Point for the S 1/16 section corner of section 30 only, falls in Sevier Bridge Reservoir; not monumented.

**80.177** Point for the corner of sections 25 and 36 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.

---

N. 0°16.3' E., on the east boundary of section 25, T. 16 S., R. 2 W.

**1.941** Point for the 1/4 section corner of section 30 only, falls in Sevier Bridge Reservoir; not monumented.

**21.950** Point for the N 1/16 section corner of section 30 only, falls in Sevier Bridge Reservoir; not monumented.

**40.098** Point for the 1/4 section corner of section 25 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.

**42.580** Point for the closing corner of sections 19 and 30, falls in Sevier Bridge Reservoir; not monumented.

**62.5395** Point for the S 1/16 section corner of section 19 only, falls in Sevier Bridge Reservoir; not monumented.

**80.117** Point for the corner of sections 24 and 25 only, T. 16 S., R. 2 W., falls in Sevier Bridge Reservoir; not monumented.

---

N. 0°16.3' E., on the east boundary of section 24, T. 16 S., R. 2 W.

RETRACEMENT OF A PORTION OF THE WEST BOUNDARY,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****2.382**

The 1/4 section corner of section 19 only, monumented with an aluminum post, 2 1/2 ins. diam., set 2 ins. above ground, with aluminum cap marked as described in the official record of the 1991 resurvey by F.D. Reynolds.

**22.340**

Point for the N 1/16 section corner of section 19 only; not monumented.

**40.138**

The 1/4 section corner of section 24 only, T. 16 S., R. 2 W., monumented with an iron post, 2 1/2 ins. diam., set 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch.

---

N. 0°28.6' E., beginning new measurement.

**2.160**

The closing corner of sections 18 and 19 only, monumented with an iron post, 2 1/2 ins. diam., set 2 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey by G.B. Hatch.

From this corner

The corner of sections 13 and 24 only, T. 16 S., R. 2 W., monumented with an iron post, 2 1/2 ins. diam., set 8 ins. above ground, with brass cap marked as described in the official record of 1991 resurvey by F.D. Reynolds, bears N. 0°28.6' E., 38.232 chains dist.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 16 S., R. 1 W., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by Stewart and Stewart in  
1898 and the Resurvey Executed by G.B. Hatch in 1973

---

Beginning at the corner of sections 5, 6, 31, and 32, T. 16 and 17 S., R. 1 W., on the south boundary of the township, monumented with an iron post, 2 1/2 ins. diam., firmly set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

From this corner, U.S. Coast and Geodetic Survey Triangulation Station "YUBA", bears S. 56°25.3' W., 203.079 chains dist.

N. 89°38.5' W., between sections 6 and 31.

Over mountainous land, through scattered pinon and juniper growth.

**19.862**

Point for the E 1/16 section corner of sections 6 and 31, not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****39.724**

The 1/4 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. in diam., extending 10 ins. above ground, and in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°38.7' W., beginning new measurement.

**19.950**

Point for the W 1/16 section corner of sections 6 and 31, falls within the Sevier Bridge Reservoir; not monumented.

**39.900**

Point for the 80 1/16 section corner of sections 6 and 31, falls within the Sevier Bridge Reservoir; not monumented.

**79.800**

The 120 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., set 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°37.3' W., beginning new measurement.

**39.910**

The 160 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°38.4' W., beginning new measurement.

**39.970**

The 200 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°37.9' W., beginning new measurement.

**19.958**

The 220 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked:

	T16S R1W	
	<u>S31</u>	
1/16	S6	220
	T17S R1W	
	1973	

This corner was established by G.B. Hatch in 1973, but not recorded within the field note record. This corner is accepted as the 220 1/16 section corner of sections 6 and 31.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 89°38.1' W., beginning new measurement.

**19.963** The 240 1/16 section corner of sections 6 and 31, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°41.0' W., beginning new measurement.

**4.992** The closing corner of sections 6 and 31, on the west boundary of the township, hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 16 S., R. 1 W., Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by Stewart and Stewart in  
1898 and the Resurvey Executed by G.B. Hatch in 1973

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0°22.4' W., on the east boundary of section 31.

Over rolling mountainous land, through scattered pinon and juniper growth.

**20.170** Point for the S 1/16 section corner of section 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

T16S R1W  
S 1/16 |  
S31 |  
1995

The corner is located on a steep broken W slope.

**40.340** The 1/4 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°55.9' W., beginning new measurement.

**0.300** The 1/4 section corner of section 32 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

**39.935** The corner of sections 29 and 31, on the east boundary of section 31, monumented with an iron post, 2 1/2 ins. diam., extending 10 ins. above ground and in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

---

S. 89°28.9' W., on the north boundary of section 31.

Over rolling mountainous land, through scattered pinon and juniper growth.

**5.918** The closing corner of sections 29 and 30 only, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked as described in the official record of the 1973 resurvey.

**39.983** The 1/4 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°34.6' W., beginning new measurement.

**5.785** The 1/4 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°33.1' W., beginning new measurement.

**19.900** The W 1/16 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°31.1' W., beginning new measurement.

**14.108** The 80 1/16 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89°35.1' W., beginning new measurement.

**5.799** Point for the 80 1/16 section corner of section 30 only, falls within the Sevier Bridge Reservoir; not monumented.

**39.734** Point for the 120 1/16 section corner of section 31 only, falls within the Sevier Bridge Reservoir; not monumented.

**45.573** The 120 1/16 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°33.1' W., beginning new measurement.

**19.901** Point for the 140 1/16 section corner of section 30 only, falls within the Sevier Bridge Reservoir; not monumented.

**33.918** The 160 1/16 section corner of section 31 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°40.1' W., beginning new measurement.

**5.888** The 160 1/16 section corner of section 30 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

---

N. 89°32.1' W., beginning new measurement.

**33.871** Point for the 200 1/16 section corner of section 31 only, falls within the Sevier Bridge Reservoir; not monumented.

**39.793** Point for the 200 1/16 section corner of section 30 only, falls within the Sevier Bridge Reservoir; not monumented.

**73.643** Point for the 240 1/16 section corner of section 31 only, falls within the Sevier Bridge Reservoir; not monumented.

**77.814** Point for the closing corner of sections 30 and 31, on the west boundary of the township, hereinbefore described.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the closing corner of sections 29 and 30, on the north boundary of section 31.

N. 0°38.9' W., between sections 29 and 30.

Over rolling mountainous land, through lightly scattered pinon and juniper growth.

**20.129** The S 1/16 section corner of sections 29 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°35.1' W., beginning new measurement.

**20.180** The 1/4 section corner of sections 29 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°18.7' W., beginning new measurement.

**40.120** The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

S. 89°24.4' W., between sections 19 and 30.

Over rolling mountainous land, through pinon and juniper growth.

**20.108** Point for the E 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked.

	T16S R1W
E 1/16	<u>S19</u>
	S30
	1995

Set a steel fence post alongside the aluminum post.

**40.216** The 1/4 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

- N. 89°25.5' W., beginning new measurement.
- 39.730** The 80 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
- 
- N. 89°26.0' W., beginning new measurement.
- 19.878** The 100 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
- 
- N. 89°25.9' W., beginning new measurement.
- 19.883** The 120 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
- 
- N. 89°25.5' W., beginning new measurement.
- 39.748** The 160 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
- 
- N. 89°26.5' W., beginning new measurement.
- 19.860** The 180 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
- 
- N. 89°28.5' W., beginning new measurement.
- 19.888** The 200 1/16 section corner of sections 19 and 30, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.
- 
- N. 89°27.1' W., beginning new measurement.
- 36.762** Point for the closing corner of sections 19 and 30, on the west boundary of the township, hereinbefore described.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the corner of sections 19, 20, 29, and 30.

N. 1°55.0' W., between sections 19 and 20.

Over gentle rolling land.

**20.476** The S 1/16 section corner of sections 19 and 20, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 1°55.0' W., beginning new measurement.

**20.471** The 1/4 section corner of sections 19 and 20, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°53.6' W., beginning new measurement.

**19.608** The N 1/16 section corner of section 19 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 0°53.5' W., beginning new measurement.

**1.135** The N 1/16 section corner of section 20 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

**19.614** The corner of sections 18 and 19 only, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

S. 89°18.0' W., between sections 18 and 19.

Over rolling land.

**20.486** Point for the E 1/16 section corner of sections 18 and 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T16S R1W

E 1/16

S18

S19

1995

Set a steel fence post alongside the aluminum post.

The corner is located on a NW slope.

- 40.972** The 1/4 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°30.2' W., beginning new measurement.

- 19.802** The W 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°29.4' W., beginning new measurement.

- 19.815** The 80 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°30.3' W., beginning new measurement.

- 19.802** The 100 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°28.8' W., beginning new measurement.

- 19.805** The 120 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°29.4' W., beginning new measurement.

- 39.614** The 160 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 89°29.5' W., beginning new measurement.

39.607

The 200 1/16 section corner of sections 18 and 19, monumented with an iron post, 2 1/2 ins. diam., extending 8 ins. above ground, with brass cap marked as described in the official record of the 1973 resurvey.

N. 89°28.8' W., beginning new measurement.

34.114

The closing corner of sections 18 and 19, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 19,  
T. 16 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 19 and 30.

N. 1°57.8' W., on the N - S center line of section 19.

Over rolling mountainous land, through scattered pinon and juniper growth.

20.730

Point for the center S 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
C  
S 1/16 | S19  
C  
1995

Set a steel fence post alongside the aluminum post.

41.460

Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:

T16S R1W  
C 1/4 S19  
1995

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope.

THE SUBDIVISION OF SECTION 19,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

60.782

Point for the center N 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
C  
N 1/16 | S19  
C  
1995

Set a steel fence post alongside the aluminum post.

80.104

The 1/4 section corner of sections 18 and 19.

From the 1/4 section corner of sections 19 and 20.

N. 89°52.7' W., on the E - W center line of section 19.

Over rolling mountainous land, through scattered pinon and juniper growth.

19.400

Point for the center E 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
C — E 1/16 — C  
S19  
1995

Set a steel fence post alongside the aluminum post.

40.260

The center 1/4 section corner of section 19.

79.930

Point for the center 80 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
C — 80 1/16 — C  
S19  
1995

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 19,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner is located on a SW slope.

**99.765**

Point for the center 100 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
C — 100 1/16 — C  
S19  
1995

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level sagebrush flat.

**119.600**

Point for the center 120 1/16 section corner of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
C — 120 1/16 — C  
S19  
1995

Set a steel fence post alongside the aluminum post.

The corner is located in rolling foothills.

**179.105**

Point for the center 180 1/16 section corner of section 19; not monumented.

**234.365**

The 1/4 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

---

From the center E 1/16 section corner of section 19.

N. 2°29.8' W., on the N - S center line of the NE 1/4 of section 19.

**19.480**

Point for the NE 1/16 section corner at intersection with the E - W center line of the NE 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 19,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T16S R1W  
NE 1/16 S19  
1995

Set a steel fence post alongside the aluminum post.

**38.957** The E 1/16 section corner of sections 18 and 19.

From the N 1/16 section corner of section 19 only, on the east boundary of section 19.

S. 89°43.2' W., on the E - W center line of the NE 1/4 of section 19.

**19.943** The NE 1/16 section corner of section 19.

**40.616** The center N 1/16 section corner of section 19.

From the E 1/16 section corner of sections 19 and 30.

N. 0°55.5' W., on the N - S center line of the SE 1/4 of section 19.

**20.596** Point for the SE 1/16 section corner at intersection with the E - W center line of the SE 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
SE 1/16 S19  
1995

Set a steel fence post alongside the aluminum post.

**41.184** The center E 1/16 section corner of section 19.

From the S 1/16 section corner of sections 19 and 20.

S. 89°46.1' W., on the E - W center line of the SE 1/4 of section 19.

**19.754** The SE 1/16 section corner of section 19.

**40.238** The center S 1/16 section corner of section 19.

THE SUBDIVISION OF SECTION 19,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the 100 1/16 section corner of sections 19 and 30.

N. 1°51.2' W., on the 100 1/16 line of the SW 1/4 of section 19.

**20.501**

Point for the S 100 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
S  $\frac{1}{16}$  100  
S19  
1995

Set a steel fence post alongside the aluminum post.

**40.997**

The center 100 1/16 section corner of section 19.

---

From the 180 1/16 sec. cor. of secs. 19 and 30.

N. 0°41.1' W., on the 180 1/16 line of the SW 1/4 of section 19.

**20.186**

Point for the S 180 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T16S R1W  
S  $\frac{1}{16}$  180  
S19  
1995

Set a steel fence post alongside the aluminum post.

**40.372**

Point for the center 180 1/16 section corner of section 19.

---

From the center S 1/16 section corner of section 19.

N. 89°39.5' W., on the E - W center line of the SW 1/4 of section 19.

**59.556**

The S 100 1/16 section corner of section 19.

**138.971**

The S 180 1/16 section corner of section 19.



THE SUBDIVISION OF SECTION 19,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**194.926**

Point for the S 1/16 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

From the center 100 1/16 section corner of section 19.

N. 1°49.3' W., on the 100 1/16 line of the NW 1/4 of section 19.

**19.520**

Point for the N 100 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

		T16S R1W	
N	$\frac{1}{16}$	100	
	S19		
	1995		

Set a steel fence post alongside the aluminum post.

**39.021**

The 100 1/16 section corner of sections 18 and 19.

From the center 120 1/16 section corner of section 19.

N. 1°46.4' W., on the 120 1/16 line of the NW 1/4 of section 19.

**19.586**

Point for the N 120 1/16 section corner at intersection with the E - W center line of the NW 1/4 of section 19.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

		T16S R1W	
N	$\frac{1}{16}$	120	
	S19		
	1995		

Set a steel fence post alongside the aluminum post.

**39.156**

The 120 1/16 section corner of sections 18 and 19.

From the center N 1/16 section corner of section 19.

N. 89°41.2' W., on the E - W center line of the NW 1/4 of section 19.

THE SUBDIVISION OF SECTION 19,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****59.462**

The N 100 1/16 section corner of section 19.

**79.281**

The N 120 1/16 section corner of section 19.

**193.332**

Point for the N 1/16 section corner of section 19 only, on the west boundary of the township, hereinbefore described.

---

The Subdivision of Section 30,  
T. 16 S., R. 1 W., Salt Lake Meridian, Utah

---

From the 1/4 section corner of section 30 only, on the south boundary of the section.

N. 0°44.0' W., on the N - S center line of section 30.

**20.376**

Point for the center S 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:

T16S R1W  
C  
S 1/16 | S30  
C  
1995

Set a steel fence post alongside the aluminum post.

The corner is located on a SW slope, 25 lks. dist., N of a draw, drains NW.

**40.752**

Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
C 1/4 S30  
1995

Set a steel fence post alongside the aluminum post.

The corner is located in a small draw, drains SW.

**60.163**

Point for the center N 1/16 section corner of section 30.

THE SUBDIVISION OF SECTION 30,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
C  
N 1/16 | S30  
C  
1995

Set a steel fence post alongside the aluminum post.

The corner is located on the SW slope of a hill.

80.282

The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

N. 89°45.6' W., on the E - W center line of section 30.

Over rolling mountainous land, through scattered pinon and juniper growth.

39.932

The center 1/4 section corner of section 30.

59.817

Point for the center W 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
C W 1/16 C  
S30  
1995

Set a steel fence post alongside the aluminum post.

79.702

Point for the center 80 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
C 1/16 80  
S30  
1995

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 30,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The corner is located in the head of a small draw, drains SW.

119.472

Point for the center 120 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
C	$\frac{1/16}{S30}$	120
	1995	

Set a steel fence post alongside the aluminum post.

139.357

Point for the center 140 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
C	$\frac{1/16}{S30}$	140
	1995	

Set a steel fence post alongside the aluminum post.

159.242

Point for the center 160 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
C	$\frac{1/16}{S30}$	160
	1995	

Set a steel fence post alongside the aluminum post.

179.127

Point for the center 180 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
C	$\frac{1/16}{S30}$	180
	1995	

THE SUBDIVISION OF SECTION 30,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

**199.012** Point for the center 200 1/16 section corner of section 30, falls within the Sevier Bridge Reservoir; not monumented.

**236.396** Point for the 1/4 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

---

From the W 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°43.0' W., on the N - S center line of the SW 1/4 of section 30.

**20.340** Point for the SW 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
SW 1/16 S30  
1995

Set a steel fence post alongside the aluminum post.

The corner is located in a large sandy draw, drains SW.

**40.679** The center W 1/16 section corner of section 30.

---

From the point for the 80 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°41.3' W., on the 80 1/16 section line of the SW 1/4 of section 30.

**20.303** Point for the S 80 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
S 1/16 80  
S30  
1995

THE SUBDIVISION OF SECTION 30,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling W slope.

**40.605** The center 80 1/16 section corner of section 30.

---

From the 120 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°41.1' W., on the 120 section line of the SW 1/4 of section 30.

**20.257** Point for the S 120 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
S	<u>1/16</u>	120
	S30	
	1995	

Set a steel fence post alongside the aluminum post.

**40.485** The center 120 1/16 section corner of section 30.

---

From the point for the 140 1/16 section corner of section 30 only, on the south boundary of the section.

N. 0°40.4' W., on the 140 section line of the SW 1/4 of section 30.

**20.220** Point for the S 140 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
S	<u>1/16</u>	140
	S30	
	1995	

Set a steel fence post alongside the aluminum post.

The corner falls on nearly level desert land.

THE SUBDIVISION OF SECTION 30,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**40.411**

The center 140 1/16 section corner of section 30.

From the center S 1/16 section corner of section 30.

N. 89°39.4' W., on the E - W center line of the SW 1/4 of section 30.

**19.893** The SW 1/16 section corner of section 30.

**39.782** The S 80 1/16 section corner of section 30.

**79.561** The S 120 1/16 section corner of section 30.

**99.455** The S 140 1/16 section corner of section 30.

**196.834** The point for the S 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

From the center 120 1/16 section corner of section 30.

N. 0°39.8' W., on the 120 section line of the NW 1/4 of section 30.

**19.654** Point for the N 120 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
	<u>1/16</u>	120
N	S30	
	1995	

Set a steel fence post alongside the aluminum post.

**39.979** The 120 1/16 section corner of sections 19 and 30.

From the center 180 1/16 section corner of section 30.

N. 0°35.8' W., on the 180 section line of the NW 1/4 of section 30.

**19.837** Point for the N 180 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 30.

THE SUBDIVISION OF SECTION 30,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
N	<u>1/16</u>	180
	S30	
	1995	

Set a steel fence post alongside the aluminum post.

**40.325** The 180 1/16 section corner of sections 19 and 30.

---

From the point for the center 200 1/16 section corner of section 30.

N. 0°36.0' W., on the 200 1/16 section line of the NW 1/4 of section 30.

**19.897** Point for the N 200 1/16 section corner, at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T16S R1W	
N	<u>1/16</u>	200
	S30	
	1995	

Set a steel fence post alongside the aluminum post.

The corner is located 50 lks. dist., E of the high water mark of Sevier Bridge Reservoir, bears NW and SE.

**40.427** The 200 1/16 section corner of sections 19 and 30.

---

From the center N 1/16 section corner of section 30.

N. 89°35.2' W., on the E - W center line of the NW 1/4 of section 30.

**79.516** The N 120 1/16 section corner of section 30.

**139.148** The N 180 1/16 section corner of section 30.

**159.035** The N 200 1/16 section corner of section 30.

**196.113** Point for the N 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.



THE SUBDIVISION OF SECTION 31,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The Subdivision of Section 31  
T. 16 S., R. 1 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 6 and 31 on the south boundary of the township, hereinbefore described.

N. 0°50.8' W., on the N - S center line of section 31.

Over mountainous land, through scattered pinon and juniper growth.

**20.149** Point for the center S 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:

T16S R1W  
C  
S 1/16 | S31  
C  
1995

The corner is located on the NE slope of a hill, 50 lks. dist., N of the top of a ridge, bears NW and SE.

**40.298** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
C 1/4 S31  
1995

Set a steel fence post alongside the aluminum post.

**59.982** Point for the center N 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
C  
N 1/16 | S31  
C  
1995

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 31,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The corner is located on a gentle NW slope.

79.666

The 1/4 section corner of section 31 only, on the north boundary of the section.

From the 1/4 section corner of section 31 only, on the east boundary of the section.

N. 89°43.4' W., on the E - W center line of section 31.

20.027

Point for the center E 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
C E 1/16 C  
S31  
1995

Set a steel fence post alongside the aluminum post.

40.054

The center 1/4 section corner of section 31.

59.974

Point for the center W 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
C W 1/16 C  
S31  
1995

Set a steel fence post alongside the aluminum post.

79.894

Point for the 80 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

119.734

Point for the center 120 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

159.574

Point for the center 160 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

199.414

Point for the center 200 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

THE SUBDIVISION OF SECTION 31,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**219.334**

Point for the center 220 1/16 section corner of section 31, falls within the Sevier Bridge Reservoir; not monumented.

**243.836**

Point for the 1/4 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

---

From the point for the E 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°36.6' W., on the N - S center line of the SE 1/4 of section 31.

**20.159**

Point for the SE 1/16 section corner, at intersection with the E - W center line of the SE 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T16S R1W  
SE 1/16 S31  
1995

Set a steel fence post alongside the aluminum post.

**40.318**

The center E 1/16 section corner of section 31.

---

From the S 1/16 section corner of section 31 only, on the east boundary of the section.

N. 89°40.4' W., on the E - W center line of the SE 1/4 of section 31.

**19.945**

The SE 1/16 section corner of section 31.

**39.890**

The center S 1/16 section corner of section 31.

---

From the point for the W 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°48.5' W., on the N - S center line of the SW 1/4 of section 31.

**20.140**

Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 31,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T16S R1W  
SW 1/16 S31  
1995

Set a steel fence post alongside the aluminum post.

40.274 The center W 1/16 section corner of section 31.

From the 120 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°41.7' W., on the 120 1/16 section line of the SW 1/4 of section 31.

20.108 Point for the S 120 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
S    1/16    120  
     S31  
     1995

Set a steel fence post alongside the aluminum post.

The corner is located on a steep N slope, 60 lks. dist., S of the high water mark of the Sevier Bridge Reservoir, bears NE and SW in cove.

40.194 Point for the center 120 1/16 section corner of section 31.

From the 220 1/16 section corner of sections 6 and 31, on the south boundary of the township, hereinbefore described.

N. 0°22.1' W., on the 220 1/16 section line of the SW 1/4 of section 31.

20.010 Point for the S 220 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T16S R1W  
S    1/16    220  
     S31  
     1995

THE SUBDIVISION OF SECTION 31,  
T. 16 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located 55 lks. dist., S of the high water mark of Sevier Bridge Reservoir, bears E and W.

**40.016** The point for the center 220 1/16 section corner of section 31.

---

From the center S 1/16 section corner of section 31.

N. 89°40.9' W., on the E - W center line of the SW 1/4 of section 31.

**19.934** The SW 1/16 section corner of section 31.

**79.736** The S 120 1/16 section corner of section 31.

**179.454** The S 220 1/16 section corner of section 31.

**204.182** Point for the S 1/16 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

---

From the point for the center 80 1/16 section corner of section 31.

N. 0°46.9 W., on the N 80 1/16 section line of the NW 1/4 of section 31.

**39.485** The 80 1/16 section corner of section 31 only on the north boundary of the section.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Philip Tobler	Surveying Technician

## CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *1st day of March, 1993*, I have *retraced a portion of the west boundary, dependently resurveyed portions of the south boundary, and subdivisional lines, and subdivided sections 19, 30, and 31, in Township 16 South, Range 1 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 10, 1997

Date

*Ferrel D. Reynolds*

(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *retracement of a portion of the west boundary, dependent resurvey of portions of the south boundary, and subdivisional lines, and the subdivision of sections 19, 30, and 31, in Township 16 South, Range 1 West, Salt Lake Meridian, Utah,*

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 24, 1997

Date

*Daniel W. Welch*

(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

A PORTION OF

THE SOUTH AND WEST BOUNDARIES

A PORTION OF

THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS

8, 9, 17, 20, 30 AND 31

IN

TOWNSHIP 14 SOUTH, RANGE 1 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds*  
*Cadastral Surveyor*

Under special instructions dated *April 8, 1993*, approved April 8, 1993, which provided for the surveys included under Group Number 797, and assignment instructions dated April 8, 1993.

Survey commenced *April 28, 1993*

Survey completed *April 19, 1994*



## INDEX DIAGRAM

Township 14 South , Range 1 West

6	5	4	3	2	1
	28 27	16			
27 7	8 15	10 9 9	10	11	12
	26	14			
18 25	13 17	16 8	15	14	13
	25				
19 23	20	21	22	23	24
22 21	21				
5	12				
4 30 20	29	28	27	26	25
19	11 18				
3					
31 17	32	33	34	35	36
7 6					

The Subdivision of Section 8.....Page 28

The Subdivision of Section 9.....Page 30

The Subdivision of Section 17.....Page 32

The Subdivision of Section 20.....Page 33

The Subdivision of Section 30.....Page 34

The Subdivision of Section 31.....Page 39

## TOWNSHIP 14 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines, and the subdivision of sections 8, 9, 17, 20, 30 and 31, in Township 14 South, Range 1 West, Salt Lake Meridian, Utah.

**History of Surveys**

Surveyed by			Retr. or Resurveyed by	
NORTH BOUNDARY				
Portion	C. Mogo	1856	E.W. Koeber	1884
Portion	E.W. Koeber	1884		
Portion	Stewart & Stewart	1898		
SOUTH BOUNDARY				
Portion	C. Mogo	1856	Stewart & Stewart	1898
Portion	Stewart & Stewart	1898		
EAST BOUNDARY				
All	C. Mogo	1856	A.D. Ferron	1882
All				
WEST BOUNDARY				
Portion	F. Dickert	1871	Stewart & Stewart Stewart & Heist R.A. Zaninovich	1898 1912 1991
All	Stewart & Stewart	1898		
Portion				
Portion				
SUBDIVISION				
Portion	C. Mogo	1856	Stewart & Stewart	1898 1991
Portion	Stewart & Stewart	1898		
Portion				

The closing subdivisional lines into the west boundary of T. 15 S., R. 1 1/2 W., were surveyed by Stewart and Stewart in 1898.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 797, dated April 8, 1993.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

## TOWNSHIP 14 SOUTH, RANGE 1 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 28, 29, 32, and 33, as determined by a tie made to U.S. Coast and Geodetic Survey triangulation station "Cedar" is as follows:

Latitude 39°33'26.37" N. Longitude 111°56'48.80" W.  
N.A.D. 1927

The mean magnetic declination as determined from the U.S. Geological Survey Magnetic Declination Map of 1990 is 14° E.

---

Dependent Resurvey of a Portion of the West Boundary,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

---

Reestablishment of the Survey executed by F. Dickert in 1871,  
the Resurvey by Stewart and Stewart in 1898,  
and the Resurvey by Stewart and Heist in 1912

---

Beginning at the point for the closing corner of sections 2 and 31, Townships 14 and 15 South, Ranges 1 and 1 1/2 West respectively, at proportionate distance. No remaining evidence of the original corner was found; not monumented.

From this point:

The point for the corner of sections 1 and 12 only, T. 15 S., R. 2 W., at proportionate distance. No remaining evidence of the original corner or intervening corners were found, bears S. 0°10.5' W., 52.293 chains dist.

From this same point:

The closing corner of sections 2 and 11, on the west boundary of T. 15 S., R 1 1/2 W, monumented with a sandstone, 18x12x4 ins., firmly set and plainly marked with 1 groove on the N and 5 grooves on the S edge, with a CC on the E face, bears S. 0°14.1' W., 87.414 chains dist.; not remonumented.

N. 0°10.5' E., on the east boundary of section 1, T. 15 S., R. 2 W.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Over gently rolling cultivated land.

**20.196** Point for the S 1/16 section corner of section 31 only; T. 14 S., R. 2 W.; not monumented.

**28.209** Point for the corner of sections 1 and 36 only, Townships 14 and 15 South, Range 2 West, at proportionate distance. No remaining evidence of the original corner was found; not monumented.

---

N. 0°16.5' E., on the east boundary of section 36, T. 14 S., R. 2 W.

**12.183** Point for the W 1/4 section corner of section 31 only, at proportionate distance. No remaining evidence of the original corner was found; not monumented.

**40.100** Point for the E 1/4 section corner of section 36, T. 14 S., R. 2 W., at proportionate distance. No remaining evidence of the original corner was found; not monumented.

**52.575** Point for the closing corner of sections 30 and 31, on the west boundary of the township, as determined from the record bearing and distance from the original bearing tree ( S. 37°30' E., 1.20 chains dist.) and then with a cardinal offset to intersect the west boundary ( S. 89°52.8' E., 0.156 chains dist.) No remaining evidence of the original rock corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

		T14S	
		R2W	R1W
S36		S30	C
		S31	C
		1993	

Set a steel fence post alongside the aluminum post.

From which, the original bearing tree with new bearing and distance:

A juniper, 16 ins. diam., with scribe marks visible, bears  
S. 31°06' E., 1.11 chains distance.

**72.241** Point for the S 1/16 section corner of section 30 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T14S  
R2W R1W  
| S 1/16  
| S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gently rolling W slope in a fence corner, 4 strand barbwire, bears N and E, in sagebrush and scattered juniper.

80.411

The corner of section 25 and 36 only, T. 14 S., R. 2 W., monumented with a Juab County aluminum post, 2 1/2 ins. in diam., extending 6 ins. out of ground, with the original marked stone found alongside, with aluminum cap marked.

JUAB COUNTY  
T14S  
R2W R1W  
S25 | S30  
S36 |  
1986

The corner is located in a fence corner, 4 strand barbwire, bears N and W, in sagebrush and scattered juniper growth.

N. 0°09.6' E., on the east boundary of section 25, T. 14 S., R. 2 W.

11.496

Point for the W 1/4 section corner of section 30 only, at proportionate distance, no remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S  
R2W R1W  
| 1/4  
| S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 10 lks. E of a fence line, 4 strand barbwire, bears N and S, on gentle W slope in sagebrush and scattered juniper growth.

31.162

Point for the N 1/16 section corner of section 30 only; not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS  
40.041

The 1/4 section corner of section 25 only, T. 14 S., R. 2 W., monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap marked.

JUAB COUNTY

T14S

R2W R1W

1/4

S25

1986

The corner is located in a fence corner, 4 strand barbwire, bears N, E, S, and W on a gentle W slope in sagebrush.

N. 0°03.2' W., beginning new measurement.

10.787

The closing corner of sections 19 and 30, monumented with an aluminum post, 2 1/2 ins. diam., extending 8 ins. above ground, with Juab County aluminum cap, marked:

JUAB COUNTY

T14S

R2W S25 | S19 R1W  
S30

1986

The corner is located 5 lks. E of a fence line, 4 strand barbwire, bears N and S, on gently rolling land.

From this corner:

The corner of sections 24 and 25, T. 14 S., R. 2 W., bears N. 0°03.2' W., 29.268 chains dist., monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap, marked:

JUAB COUNTY

T14S

R2W S24 | R1W  
S25

1986

The corner is located in a fence line, 4 strand barbwire, bears N and S.

Dependent Resurvey of a Portion of the South Boundary,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

## Reestablishment of the Survey by Stewart and Stewart in 1898

From the corner of sections 5, 6, 31, and 32, Township 14 and 15 South, Range 1 West, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground. This corner is accepted as a careful and faithful perpetuation of the position of the original corner. The aluminum cap is marked:

JUAB COUNTY  
T14S R1W  
S31 | S32  
S6 | S5  
T15S  
1990

No remaining evidence of the original rock corner or bearing trees were found.

The corner is located 15 lks. S of a fence corner, 4 strand barbwire, bears N, E and W, on gentle E slope in reseeded area.

N. 89°59.2' W., on the south boundary of section 31.

Over mountain land, through juniper and pinon growth.

11.00 Ridge, bears NE and SW

39.519 The 1/4 section corner of sections 6 and 31, monumented with a limestone, 20x12x4 ins., firmly set and plainly marked 1/4 on the N face.

From which the original bearing tree.

A juniper, 10 ins. diam., bears S. 65° W., 34 lks. dist., marked  
1/4 S6 BT.

No remaining evidence of the other original bearing tree was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

1/4 T14S R1W  
S31  
S6  
T15S R1W  
1993

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Raise a mound of stone N of the corner.

The corner is located on a SE slope, in pinon and juniper growth.

S. 89°32.6' W., beginning new measurement.

22.15 Top of high ridge or divide, bears NE and SW.

38.824 The closing corner of sections 1 and 6, T. 15 S., Rs. 1 and 1 1/2 W., monumented with a red sandstone, 18x14x8 ins., firmly set and plainly marked with 6 notches on the E, W, and S sides, with R 1 W on the E side and R 1 1/2 on the W side.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W	
<u>S32</u>	
S1	S6
C	C
R1 1/2	R1W
T15S	
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone S of the corner.

The corner is located on a SW slope in scattered juniper growth.

79.928 Point for the 120 1/16 section corner of section 31 only; not monumented.

99.910 Point for the 140 1/16 section corner of section 31 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W		
<u>1/16</u>	<u>S31</u>	<u>140</u>
T15S	R1	1/2W
1993		

Set a steel fence post alongside the aluminum post.



DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

167.451

The corner is located on a gentle W slope in native grasses.

Point for the closing corner of sections 2 and 31, Townships, 14 and 15 South, Ranges 1 and 1 1/2 West, hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah

Reestablishment of the Survey by Stewart and Stewart in 1898.

From the W 1/4 section corner of section 15 only, monumented with a limestone, 18x10x10 ins., firmly set in a mound of stone and plainly marked 1/4 on the W face.

From which the original bearing trees;

A juniper, 10 ins. diam., bears N. 85° E., 18 lks. dist., marked  
S 15 BT.

A juniper, 12 ins. diam., bears N. 50° W., 22 lks. dist., marked  
S 16 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T14S R1W  
1/4  
| S15  
1993

The corner is located on a E slope in juniper growth.

N. 0°33.3' W., on the west boundary of section 15.

Over mountain land, through juniper and pinon growth.

37.995

The closing corner of sections 9 and 16, monumented with a trachyte stone, 18x10x8 ins., firmly set and plainly marked CC on the W face, 4 grooves on the S and 3 grooves on the E faces.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S	R1W	
CC	<u>S9</u>		S15
	S16		
	1993		

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located in the bottom of a draw, drains NE.

40.369

The corner of sections 10 and 15 only, monumented with a granite stone, 16x8x8 ins., firmly set and plainly marked with, 4 notches on the S and 3 notches on the E edges.

From which the original bearing tree:

A juniper, 8 ins. diam., bears S. 6° E., 69 lks. dist.,  
with scribe marks dimly visible.

No remaining evidence of the other original bearing trees were found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S	R1W	
S9		<u>S10</u>	
		S15	
	1993		

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone E of the corner.

The corner is located 3 lks. S of a fence line, 3 strand barbwire, bears E and W, on E slope in juniper growth.

---

N. 0°36.3' W., on the west boundary of section 10.

Over mountain land, through sagebrush and juniper growth.

37.166

Point for the E 1/4 section corner of section 9 only, at midpoint between closing corners.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  
S 9  
1993

Raise a mound of stone W of the corner.

The corner is located on a steep SW slope in buckbrush and juniper growth.

**39.760**

Point for the 1/4 section corner of section 10 only, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  
S10  
1993

Raise a mound of stone E of the corner.

The corner is located on a SW slope in buckbrush and juniper growth.

**56.936**

Point for the N 1/16 section corner of section 9 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
N 1/16  
S9  
1993

The corner is located on a SE slope in bitterbrush and scattered juniper growth.

**76.706**

The closing corner of sections 4 and 9, monumented with a conglomerate stone, 15x8x6 ins., firmly set and plainly marked CC on the W face and 5 grooves on the S and 3 grooves on E face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T14S R1W		
C	S4	S10
C	S9	
1993		

Deposit the marked stone alongside the aluminum post.

The corner is located on a broken SE slope in bitterbrush and juniper growth.

**79.520** The corner of sections 3 and 10, monumented with a granite stone, 16x10x8 ins., firmly set and plainly marked with 5 notches on the S and 3 notches on the E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T14S R1W		
S4	S3	S10
	S10	
1993		

Deposit the marked stone alongside the aluminum post.

No remaining evidence of the original bearing tree was found.

The corner is located on a E slope in bitterbrush and juniper growth.

From the corner of sections 28, 29, 32, and 33, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of ground, and is accepted as a careful and faithful perpetuation of the position of the original corner, with the aluminum cap marked:

JUAB COUNTY		
T14S R1W		
S29	S28	S33
S32	S33	
1990		

The corner is located in a fence corner, 4 strand barbwire, bears N, S, and W.

No remaining evidence of the original rock corner or bearing trees were found.

N. 0°10.2' W., between sections 28 and 29.

Over rolling bench land, through reseed area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.615

The 1/4 section corner of sections 28 and 29, monumented with a sandstone, 24x14x8 ins., firmly set in a mound of stone and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, with aluminum cap marked:

T14S R1W  
1/4  
S29 | S28  
1993

Deposit the marked stone alongside the aluminum post.

No remaining evidence of the original bearing trees were found.

The corner is located 3 lks. E of a netwire fence line, bears N and S, on a S slope in native grasses.

N. 0°42.8' W., beginning new measurement.

20.040

Point for the N 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
N 1/16  
S29 | S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 17 lks. W of a netwire fence line, bears N and S, on rolling E slope in cultivated land.

40.080

The corner of sections 20 and 29, monumented with a netwire fence corner, bears S and W, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T14S R1W	
<u>S20</u>	S28
S29	
1993	

The corner is located on a gently rolling E slope, with cultivated land to the E and N of the corner.

From the E 1/4 section corner of section 17 only, monumented with a blue limestone, 16x8x6 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W	
1/4	
S17	
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle E slope in juniper growth.

N. 0°38.8' W., on the east boundary of section 17.

40.035

The corner of sections 8, 9, 16 and 17, monumented with a limestone, 18x10x8 ins., firmly set in a mound of stone and plainly marked with, 4 notches on S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W	
<u>S8</u>	<u>S9</u>
S17	S16
1993	

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a NE slope in burned area.

N. 89°33.2' E., between sections 9 and 16.

Over mountainous land, through burned area.

39.833

The 1/4 section corner of sections 9 and 16, monumented with a limestone, 18x6x4 ins., firmly set and plainly marked 1/4 on the N face.

From which the original bearing tree.

A juniper, 10 ins. diam., bears N. 46° W., 3 lks. dist., marked with a blaze.

No remaining evidence of the other original bearing tree was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

	T14S R1W
1/4	<u>S9</u>
	S16
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located 1 chain S of a firebreak, bears E and W, on SW slope in juniper growth.

S. 89°31.3' E., beginning new measurement.

38.697

The closing corner of sections 9 and 16.

From the corner of sections 8, 9, 16, and 17.

N. 0°16.2' W., between sections 8 and 9.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Over mountainous land, through burned area and juniper growth.

39.482

The 1/4 section corner of sections 8 and 9, monumented with a trachyte stone, 18x8x6 ins., firmly set and plainly marked 1/4 on the W face.

From which the original bearing trees:

A juniper, 10 ins. diam., bears S. 70° E., 15 lks. dist.,  
marked 1/4 S9 BT.

A juniper, 10 ins. diam., bears S. 53° W., 36 lks. dist., marked  
1/4 S8 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/4  
S8 | S9  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located on a S slope in juniper growth.

N. 0°33.3' W., beginning new measurement.

19.987

Point for the N 1/16 section corner of sections 8 and 9; not monumented.

39.974

The corner of sections 4, 5, 8 and 9, monumented with a granite stone, 18x9x6 ins., firmly set and plainly marked, with 4 notches on the E and 5 notches on S edges.

From which the original bearing tree.

A juniper, 12 ins. diam., bears S. 70° W., 60 lks. dist., marked with faint  
scribe marks.

No remaining evidence of the other original bearing tree was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T14S R1W  
S5 | S4  
S8 | S9  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located on a SE slope in burned area.

From this corner, U.S. Coast and Geodetic Survey triangulation station "CEDAR",  
monumented with a standard bronze cap, bears N. 13°33.4' E., 55.987 chains distance.

S. 89°28.2' E., between sections 4 and 9.

Over mountain land, through juniper and burned areas.

**19.786** Point for the W 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum  
cap marked:

T14S R1W  
W 1/16 S4  
S9  
1993

from which:

A small spring drains S, bears N. 78°47' W., 2.02 chains dist.

Raise a mound of stone N of the corner.

The corner is located on a SE slope in juniper growth.

**39.572** The 1/4 section corner of sections 4 and 9, monumented with a trachyte stone, 16x8x7 ins.,  
firmly set and plainly marked, 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum  
cap marked:

T14S R1W  
1/4 S4  
S9  
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located on a W slope in burned area.

S. 89°57.7' E., beginning new measurement.

**19.341** Point for the E 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
E 1/16    S4  
          S9  
          1993

Raise a mound of stone N of the corner.

The corner is located on a S slope in native grasses and juniper growth.

**38.682** The closing corner of sections 4 and 9.

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0°38.0' E., between sections 31 and 32.

Over mountain land, through reseed area.

**39.407** The 1/4 section corner of sections 31 and 32, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground. This corner is accepted as a careful and faithful perpetuation of the position of the original corner, with the aluminum cap marked.

JUAB COUNTY  
T14S R1W  
1/4    S31 | S32  
1990

No remaining evidence of the original bearing trees were found.

The corner is located on a SE slope in railed area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 0°37.8' E., beginning new measurement.

39.519

The corner of sections 29, 30, 31, and 32, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 8 ins. out of the ground.

From which the original bearing tree.

A juniper, 12 ins. diam., bears S. 45° W., 33 lks. dist., marked  
T14S R1W S31 BT.

No remaining evidence of the other original bearing tree was found.

The aluminum cap is marked:

JUAB COUNTY	
T14S R1W	
S30	S29
S31	S32
1990	

The corner is located in a fence corner, 4 strand barbwire, bears S and E, on steep N slope in dense juniper growth.

---

From the corner of sections 28, 29, 32, and 33.

S. 89°45.5' W., between sections 29 and 32.

Over mountain land, through reseed area.

39.588

The 1/4 section corner of sections 29 and 32, monumented with a Juab County aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground. This corner is accepted as a careful and faithful perpetuation of the position of the original corner, with the aluminum cap marked.

JUAB COUNTY	
T14S R1W	
1/4	S29
	S32
1990	

No remaining evidence of the original bearing trees were found.

The corner is located in a fence line, 4 strand barbwire, bears E and W, on gentle E slope in reseed area.

---

S. 89°45.5' W., beginning new measurement.

39.593

The corner of sections 29, 30, 31, and 32.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 89°44.0' W., between sections 30 and 31.

Over mountain land, through juniper growth.

**38.875**

Point for the 1/4 section corner of sections 30 and 31, as determined from the remains of the original bearing tree.

A juniper, 10 ins. in diam., bears S. 20° W., 110 lks. dist., dimly marked:

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/4 S30  
S31  
1993

The corner is located on W slope in scattered juniper growth.

N. 89°52.8' W., beginning new measurement.

**60.933**

Point for the 100 1/16 section corner of sections 30 and 31; not monumented.

**81.244**

Point for the 120 1/16 section corner of sections 30 and 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
S30  
1/16            120  
S31  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle W slope in cultivated land.

**101.555**

Point for the 140 1/16 section corner of sections 30 and 31; not monumented.

**168.578**

The closing corner of sections 30 and 31 on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0°02.3' W., between sections 29 and 30.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Over mountain land, through juniper growth.

39.545

Point for the 1/4 section corner of sections 29 and 30, at proportionate distance; no remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, with aluminum cap marked:

T14S R1W  
1/4  
S30 | S29  
1993

The corner is located on a SE slope in juniper growth.

79.090

Point for the corner of sections 19, 20, 29, and 30, as determined from the remains of a original bearing tree. The original rock corner, a trachyte, 18x10x5 ins., plainly marked with 5 notches on the E and 2 notches on the S edges was found lying loose on top of the ground.

The original bearing tree:

A juniper, 12 ins. diam., bears N. 69° E., 108 lks. dist. marked with faint scribe marks.

No remaining evidence of the other original bearing trees were found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, with aluminum cap marked:

T14S R1W  
S19 | S20  
S30 | S29  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located 68 lks. S of an old fence line, 4 strand barbwire, bears E and W, irregularly in small draw, drains SE.

From the corner of sections 20 and 29 only.

S. 89°34.7' W., between sections 20 and 29.

Over mountain land, through reseed area and burned area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS****39.354**

The 1/4 section corner of sections 20 and 29, monumented with a limestone, 16x12x8 ins., firmly set and plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W
1/4	<u>S20</u>
	S29
	1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located 24 lks. N of a fence line, 4 strand barbwire, bears E and W irregularly, on W slope in juniper growth.

---

S. 89°03.2' W., beginning new measurement.

**39.253**

The corner of sections 19, 20, 29, and 30.

---

N. 89°58.2' W., between sections 19 and 30.

Over mountain land, through juniper growth.

**40.326**

Point for the 1/4 section corner of sections 19 and 30, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W
1/4	<u>S19</u>
	S30
	1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope in reseed area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**60.489**

Point for the W 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
W 1/16    S19  
          S30  
          1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope in sagebrush and scattered juniper growth.

**100.815**

Point for the 100 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
100 1/16    S19  
              S30  
              1993

The corner is located on a SE slope in sagebrush and scattered juniper.

**120.978**

Point for the 120 1/16 section corner of sections 19 and 30; not monumented.

**181.467**

Point for the 180 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
180 1/16    S19  
              S30  
              1993

The corner is located on a S slope in juniper growth.

**201.630**

Point for the 200 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T14S R1W

200 1/16  $\frac{S19}{S30}$   
1993

Raise a mound of stone N of the corner.

The corner is located on gentle NW slope in a burned area.

207.125

The closing corner of sections 19 and 30, on the west boundary of the township, hereinbefore described.

From the corner of sections 19, 20, 29, and 30.

N. 0°19.1' W., between sections 19 and 20.

Over mountain land, through juniper growth.

39.697

The 1/4 section corner of sections 19 and 20, monumented with a granite stone, 18x10x6 ins., firmly set and plainly marked 1/4 on the W face and witnessed by a mound of stone to the W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  
S19 | S20  
1993

Raise a mound of stone W of the corner.

Deposit the marked stone alongside the aluminum post.

The corner is located on a W slope in juniper growth.

N. 1°03.2' W., beginning new measurement.

39.75

Low ridge bears E and W.

40.775

The corner of sections 17, 18, 19 and 20, monumented with a trachyte stone, 16x10x5 ins. firmly set and plainly marked with 5 notches on the E and 3 notches on the S edges.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From which the original bearing trees:

A juniper, 12 ins. diam., bears N. 7° E., 25 lks. dist., marked  
T14S R1W S17 BT.

A juniper, 12 ins. diam., bears S. 49° E., 28 lks. dist., marked  
T14S R1W S20 BT.

A juniper, 5 in. limb, bears S. 25° W., 49 lks. dist., marked  
T14S R1W S19 BT.

A juniper, 8 ins. diam., bears N. 88°15' W., 15 lks. dist., marked  
T14S R1W S18 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W	
S18	S17
S19	S20
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a NE slope in juniper growth.

From the corner of sections 17 and 20 only, monumented with a conglomerate stone, 19x10x6 ins., firmly set and plainly marked with, 4 notches on the E and 3 notches on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W	
S17	S21
S20	
1993	

Deposit the marked stone alongside the aluminum post.

No remaining evidence of the original bearing trees were found.

Raise a mound of stone W of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located on gentle E slope.

S. 89°43.8' W., between sections 17 and 20.

Over mountain land, through juniper growth.

**39.625** Point for the 1/4 section corner of sections 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with aluminum cap marked:

	T14S R1W
1/4	<u>S17</u>
	S20
	1993

The corner is located 30 lks. N of a draw, drains E, on steep S slope in scattered juniper growth.

**79.250** The corner of sections 17, 18, 19, and 20.

---

N. 0°06.7' W., between sections 17 and 18.

Over mountain land, through juniper growth.

**39.824** The 1/4 section corner of sections 17 and 18, monumented with a quartzite stone, 14x8x6 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W
	1/4
S18	S17
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a W slope in sagebrush.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

N. 0°27.1' W., beginning new measurement.

**40.213**

The corner of sections 7, 8, 17, and 18, monumented with an aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap, marked as described in the official record of the 1991 resurvey by R. A. Zaninovich.

From the corner of sections 8, 9, 16, and 17.

S. 89°49.1' W., between sections 8 and 17.

Over mountain land, through juniper growth.

**19.720**

Point for the E 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
E 1/16  $\frac{S8}{S17}$   
1993

The corner is located on a gentle W slope in juniper growth.

**39.440**

The 1/4 section corner of sections 8 and 17, monumented with a flintstone, 20x16x12 ins., firmly set and plainly marked 1/4 on the N face, and witnessed by a mound of stone to W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  $\frac{S8}{S17}$   
1993

Raise a mound of stone W of the corner.

No remaining evidence of the original bearing trees were found.

The corner is located on a SW slope in juniper growth.

S. 89°46.0' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**  
**39.726**

The corner of sections 7, 8, 17 and 18.

---

Reestablishment of the Survey by Stewart and Stewart in 1898  
and the Resurvey by R.A. Zaninovich in 1991

---

From the 1/4 section corner of sections 7 and 8, monumented with an aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap marked and witnessed as described in the official record of the 1991 resurvey by R. A. Zaninovich.

N. 2°04.9' W., beginning new measurement.

**19.622**

Point for the N 1/16 section corner of sections 7 and 8; not monumented.

**39.244**

The corner of sections 5, 6, 7, and 8, monumented with an aluminum post, 2 1/2 ins. diam., extending 6 ins. out of the ground, with aluminum cap, marked as described in the official record of the 1991 resurvey by R. A. Zaninovich.

---

Reestablishment of the Survey by Stewart and Stewart in 1898

---

From the corner of sections 4, 5, 8, and 9.

S. 89°45.0' W., between sections 5 and 8.

Over mountain land, through juniper growth.

**39.346**

The 1/4 section corner of sections 5 and 8, monumented with a limestone, 18x12x6 ins., firmly set and plainly marked 1/4 on the N face.

From which the original bearing trees:

A juniper, 10 ins. diam., bears N. 75° W., 65 lks. dist.,  
marked 1/4 S5 BT.

A juniper 10 ins. diam., bears S. 70° W., 65 lks. dist.,  
marked 1/4 S8 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T14S R1W  
1/4  $\frac{S5}{S8}$   
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a gentle SW slope, in juniper growth.

S. 89°05.3' W., beginning new measurement.

**20.234** Point for the W 1/16 section corner of sections 5 and 8.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
W 1/16  $\frac{S5}{S8}$   
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a S slope in burned area.

**40.468** The corner of sections 5, 6, 7, and 8.

The Subdivision of Section 8,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 8 and 17.

N. 0°21.1' W., on the N - S center line of section 8.

**39.578** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C 1/4 S8  
1993

THE SUBDIVISION OF SECTION 8,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The corner is located on a W slope in juniper growth.

**59.493** Point for the center N 1/16 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with aluminum cap marked:

T14S R1W  
C  
N 1/16 | S8  
C  
1993

The corner is located on top of small spur, slopes SW in juniper growth.

**79.408** The 1/4 section corner of sections 5 and 8.

---

From the 1/4 section corner of sections 8 and 9.

S. 89°57.3' W., on the E - W center line of section 8.

**39.492** The center 1/4 section corner.

**59.136** Point for the center W 1/16 section corner; not monumented.

**78.780** The 1/4 section corner of sections 7 and 8.

---

From the point for the center W 1/16 section corner of section 8.

N. 01°12.6' W., on the N - S center line of the NW 1/4 of section 8.

**19.766** Point for the NW 1/16 section corner at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
NW 1/16 S8  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a S slope in dense juniper growth.

**39.532** The W 1/16 section corner of sections 5 and 8.

THE SUBDIVISION OF SECTION 8,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center N 1/16 section corner of section 8.

S. 89°30.8' W., on the E - W center line of the NW 1/4.

**19.939** The NW 1/16 section corner of section 8.

**39.878** Point for the N 1/16 section corner of sections 7 and 8.

---

The Subdivision of Section 9,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 9 and 16.

N. 0°36.1' W., on the N - S center line of section 9.

**39.197** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T14S R1W  
C 1/4 S9  
1993

The corner is located on a SW slope in juniper growth.

**58.989** Point for the center N 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C  
N 1/16 | S9  
C  
1993

from which:

An old fence corner, 3 strand barbwire, bears S. 32°38' W.,  
63 lks. dist., bears E and S.

The corner is located on E slope in native grasses, in partial burned area of juniper growth.

**78.781** The 1/4 section corner of sections 4 and 9.

THE SUBDIVISION OF SECTION 9,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the E 1/4 section corner of section 9 only.

S. 89°58.1' W., on the E - W center line of section 9.

**19.343** Point for the center E 1/16 section corner of section 9; not monumented.

**38.686** The center 1/4 section corner.

**58.488** Point for the center W 1/16 section corner of section 9; not monumented.

**78.290** The 1/4 section corner of sections 8 and 9.

---

From the point for the center E 1/16 section corner of section 9.

N. 0°36.1' W., on the N - S center line of the NE 1/4.

**19.781** Point for the NE 1/16 section corner at intersection with E - W center line of the NE 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
NE 1/16 S9  
1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located 20 lks. S of an old fallen fence line, 3 strand barbwire, bears E and W and 1.00 ch. W of a trail road, bears SE and NW, on S slope in native grasses and juniper growth.

**39.562** The E 1/16 section corner of sections 4 and 9.

---

From the N 1/16 section corner of section 9 only.

N. 89°59.8' W., on the E - W center line of the NE 1/4.

**19.342** The NE 1/16 section corner of section 9.

**38.684** The center N 1/16 section corner of section 9.

---



THE SUBDIVISION OF SECTION 9,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the point for the center W 1/16 section corner of section 9.

N. 0°34.6' W., on the N - S center line of the NW 1/4.

19.889

Point for the NW 1/16 section corner of section 9, at intersection with the E -W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T14S R1W  
NW 1/16 S9  
1993

The corner is located on a E slope in burned area.

39.778

The W 1/16 section corner of sections 4 and 9.

From the center N 1/16 section corner of section 9.

N. 89°45.0' W., on the E - W center line of the NW 1/4.

19.794

The NW 1/16 section corner of section 9.

39.588

The point for the N 1/16 section corner of sections 8 and 9.

The Subdivision of Section 17,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 17 and 20.

N. 0°12.3' W., on the N - S center line of section 17.

39.870

Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., on solid rock and in a mound of stone, 3 1/2 ft. base to top, with aluminum cap marked:

T14S R1W  
C 1/4 S17  
1993

The corner is located on a steep broken SE slope in scattered juniper growth.

80.011

The 1/4 section corner of sections 8 and 17.

THE SUBDIVISION OF SECTION 17,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the E 1/4 section corner of section 17 only.

S. 89°39.8' W., on the E - W center line of section 17.

**19.877** Point for the center E 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
C  $\frac{E\ 1/16}{S17}$  C  
1993

Raise a mound of stone N of the corner.

The corner is located on a NW slope in burned area.

**39.754** The center 1/4 section corner of section 17.

**79.310** The 1/4 section corner of sections 17 and 18.

---

From the center E 1/16 section corner of section 17.

N. 0°25.5' W., on the N - S center line of the NE 1/4.

**40.086** The E 1/16 section corner of sections 8 and 17.

---

The Subdivision of Section 20,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 20 and 29.

N. 0°25.1' W., on the N - S center line of section 20.

**39.614** Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone to top, with aluminum cap marked:

T14S R1W  
C 1/4 S20  
1993

THE SUBDIVISION OF SECTION 20,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post alongside the aluminum post.

The corner is located on a E slope in juniper growth.

80.004

The 1/4 section corner of sections 17 and 20.

From the E 1/4 section corner of section 20 only, monumented with a limestone, 22x12x10 ins., firmly set and plainly marked 1/4 on the W face.

From which the original bearing tree.

A juniper, 8 ins. diam., bears S. 82° E., 48 lks. dist., marked  
1/4 S21 BT.

No remaining evidence of the other original bearing was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T14S R1W  
1/4  
S20 |  
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle E slope in juniper growth.

S. 89°10.6' W., on the E - W center line of section 20.

39.636

The center 1/4 section corner.

78.814

The 1/4 section corner of sections 19 and 20.

The Subdivision of Section 30,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 30 and 31.

N. 1°05.9' W., on the N - S center line of section 30.

19.721

Point for the center S 1/16 section corner of section 30; not monumented.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.442

Point for the center 1/4 section corner, at intersection with the E - W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C 1/4 S30  
1993

The corner is located on a steep NW slope in scattered juniper.

59.198

Point for the center N 1/16 section corner of section 30; not monumented.

78.954

The 1/4 section corner of sections 19 and 30.

From the 1/4 section corner of sections 29 and 30.

N. 89°54.6' W., on the E - W center line of section 30.

39.600

The center 1/4 section corner of section 30.

59.822

Point for the center W 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
C  $\frac{W\ 1/16}{S30}$  C  
1993

100.266

Point for the center 100 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
C  $\frac{\quad}{S30}$  100  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

120.488

Point for the center 120 1/16 section corner of section 30.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
C ————— 120  
S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**140.710** Point for the center 140 1/16 section corner of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
C ————— 140  
S30  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a E slope in sagebrush and juniper growth.

**207.240** The 1/4 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

From the point for the 100 1/16 section corner of sections 30 and 31.

N. 0°43.1' W., on the N - S 100 1/16 line of the SW 1/4 of section 30.

**19.700** Point for the S 100 1/16 section corner at the intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone to top, with aluminum cap marked:

T14S R1W  
1/16  
S ————— 100  
S30  
1993

Set a steel fence post alongside the aluminum post.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

The corner is located on steep NW slope in burned area.

**39.400**

The center 100 1/16 section corner.

---

From the 120 1/16 section corner of sections 30 and 31.

N. 0°35.5' W., on the N - S 120 1/16 line of the SW 1/4 of section 30.

**19.694**

Point for the S 120 1/16 section corner at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

	T14S R1W	
	1/16	
S	_____	120
	S30	
	1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**39.388**

The center 120 1/16 section corner of section 30.

---

From the point for the 140 1/16 section corner of sections 30 and 31.

N. 0°27.9' W., on the N - S 140 1/16 line of the SW 1/4 of section 30.

**19.687**

Point for the S 140 1/16 section corner at intersection with the E - W center line of the SW 1/4 of section 30.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W	
	1/16	
S	_____	140
	S30	
	1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.374

The center 140 1/16 section corner of section 30.

From the point for the center S 1/16 section corner of section 30.

N. 89°53.8' W., on the E - W center line of the SW 1/4 of section 30.

60.801

The S 100 1/16 section corner.

81.068

The S 120 1/16 section corner.

101.335

The S 140 1/16 section corner.

168.098

The S 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

From the center W 1/16 section corner of section 30.

N. 1°01.0' W., on the N - S center line of the NW 1/4 of section 30.

19.745

Point for the NW 1/16 section corner of section 30, at intersection with the E - W center line of the NW 1/4 of section 30; not monumented.

39.490

The W 1/16 section corner of sections 19 and 30.

From the center 100 1/16 section corner of section 30.

N. 0°51.1' W., on the N - S 100 1/16 line of the NW 1/4 of section 30.

19.724

Point for the N 100 1/16 section corner at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
N ————— 100  
S30  
1993

The corner is located 60 lks. N of a dry wash, drains SW on gently rolling land in sagebrush and scattered juniper.

39.448

The 100 1/16 section corner of sections 19 and 30.

THE SUBDIVISION OF SECTION 30,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the center 120 1/16 section corner of section 30.

N 0°46.2' W., on the N - S 120 1/16 line of the NW 1/4 of section 30.

19.712

Point for the N 120 1/16 section corner at intersection with the E - W center line of the NW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

	T14S R1W	
	1/16	
N	-----	120
	S30	
	1993	

Set a steel fence post alongside the aluminum post.

The corner is located on a SE slope in native grasses and scattered juniper growth.

39.424

Point for the 120 1/16 section corner of sections 19 and 30.

From the point for the center N 1/16 section corner of section 30.

N. 89°56.5' W., on the E - W center line of the NW 1/4 of section 30.

20.192

The point for the NW 1/16 section corner.

60.577

The N 100 1/16 section corner.

80.767

The N 120 1/16 section corner.

167.197

The point for the N 1/16 section corner of section 30 only, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 31,  
T. 14 S., R. 1 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 6 and 31 on the south boundary of the township, hereinbefore described.

N. 1°05.4' E., on the N - S center line of section 31.

19.674

Point for the center S 1/16 section corner of section 31; not monumented.



THE SUBDIVISION OF SECTION 31,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.348

Point for the center 1/4 section corner, at intersection with the E - W center line; not monumented.

79.107

The 1/4 section corner of sections 30 and 31.

---

From the 1/4 section corner of sections 31 and 32.

S. 89°54.4' W., on the E - W center line of section 31.

39.201

The point for the center 1/4 section corner of section 31.

119.757

Point for the center 120 1/16 section corner of section 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T14S R1W	
	1/16	
C	<hr/>	120
	S31	
	1993	

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle W slope in native grasses.

139.896

Point for the center 140 1/16 section corner of section 31; not monumented.

207.234

The point for the 1/4 section corner of section 31 only, on the west boundary of the township, hereinbefore described.

---

From the point for the 120 1/16 section corner of section 31 only on the south boundary of the township, hereinbefore described.

N. 0°09.6' E., on the N - S 120 1/16 line of the SW 1/4 of section 31.

19.920

Point for the S 120 1/16 section corner at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, an in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 31,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T14S R1W  
1/16  
S ————— 120  
S31  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gentle W slope in native grasses.

**39.840** The center 120 1/16 section corner of section 31.

From the 140 1/16 section corner of section 31 only, on the south boundary of the township, hereinbefore described.

N. 0°04.1' W., on the N - S 140 1/16 line of the SW 1/4 of section 31.

**19.984** Point for the S 140 1/16 section corner of section 31, at intersection with the E - W center line of the SW 1/4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T14S R1W  
1/16  
S ————— 140  
S31  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gentle W slope in native grasses.

**39.968** The point for the center 140 1/16 section corner of section 31.

From the point for the center S 1/16 section corner of section 31.

S. 89°43.4' W., on the E - W center line of the SW 1/4 of section 31.

**80.240** The S 120 1/16 section corner of section 31.

**100.300** The S 140 1/16 section corner of section 31.

**167.752** The point for the S 1/16 section corner of section 31 only on the west boundary of the township, hereinbefore described.

THE SUBDIVISION OF SECTION 31,  
T. 14 S., R. 1 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

From the center 120 1/16 section corner of section 31.

N. 0°05.1' E., on the N - S 120 1/16 line of the NW 1/4 of section 31.

**40.060**

The 120 1/16 section corner of sections 30 and 31.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Gail Reynolds	Land Surveyor
Shawn Peterson	Survey Technician


## CERTIFICATE OF SURVEY

I, **Ferrel D. Reynolds, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **8th day of April, 1993**, I have dependently resurveyed a portion of the south and west boundaries, a portion of the subdivisional lines and subdivided sections 8, 9, 17, 20, 30 and 31 in Township 14 South, Range 1 West ,

of the **Salt Lake** Meridian, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 22, 1997

Date

  
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah


The foregoing field notes of the *dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines and the subdivision of sections 8, 9, 17, 20, 30 and 31 in Township 14 South, Range 1 West, Salt Lake Meridian, Utah,*

executed by **Ferrel D. Reynolds, Cadastral Surveyor**

having been critically examined and found correct, are hereby approved.

April 24, 1997

Date



(Chief Cadastral Surveyor for Utah)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF

A PORTION OF THE  
THIRD STANDARD PARALLEL SOUTH,  
A PORTION OF THE EAST BOUNDARY,  
AND THE SUBDIVISION OF SECTION 1,  
IN

TOWNSHIP 16 SOUTH, RANGE 11 EAST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Larry V. Judd*  
*Cadastral Surveyor*

Under special instructions dated *May 14, 1993*, approved *May 27, 1993*, which provided for the surveys included under Group Number *803*, Utah, and assignment instructions dated *May 24, 1993*.

Survey commenced *June 1, 1993*

Survey completed *June 3, 1993*

# INDEX DIAGRAM

Township 16 South, Range 11 East

					3 2
6	5	4	3	2	1 3
					3
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

## TOWNSHIP 16 SOUTH, RANGE 11 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the Third Standard Parallel South, a portion of the east boundary and the subdivision of section 1 in Township 16 South, Range 11 East, Salt Lake Meridian, Utah.

**History of Surveys****Surveyed by****Retr. or Resurveyed by****NORTH BOUNDARY (Third Standard Parallel South)**

All	A.D. Ferron	1880		
Portion			C.P. Sylvester	1969

**SOUTH BOUNDARY**

Portion	A.D. Ferron	1883-84		
Portion			J.T. Breckon	1892
Portion	J.T. Breckon	1895		
Portion			J.W. Dougall	1913
All			C.P. Sylvester	1969

**EAST BOUNDARY**

All	J.T. Breckon	1895		
All			J.W. Dougall	1913
All			C.P. Sylvester	1969

**WEST BOUNDARY**

All	A.D. Ferron	1883-84		
All			J.T. Breckon	1895
All			C.P. Sylvester	1969

**SUBDIVISION**

All	J.T. Breckon	1895		
All			C.P. Sylvester	1969
Portion			J.L. Thomas	1987

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 803, dated May 14, 1993.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.



## TOWNSHIP 16 SOUTH, RANGE 11 EAST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the southeast corner of section 36, T. 15 S., R. 11 E., which is also U.S. Geological Survey Triangulation Station "SEC COR 36/15S/11E", is as follows:

Latitude 39°28'09.358" N.      Longitude 110°37'34.628" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1985, is: 13 1/4° E.

---

Dependent Resurvey of a Portion of the Third Standard Parallel South,  
T. 15 S., R. 11 E., Salt Lake Meridian, Utah

---



---

Reestablishment of the Survey Executed by A.D. Ferron in 1880  
and the Resurvey by C.P. Sylvester in 1969

---

Beginning at the southeast corner of section 36, T. 15 S., R. 11 E., monumented with an iron post, 3 1/2 ins. diameter, firmly set, projecting 12 ins. above ground, with the brass cap marked as described in the official record of the 1969 resurvey.

This corner falls on a finger ridge that slopes off into a draw to the west that drains SW.

A railroad tie, 6x6x48 ins. above ground, bears W, 5 lks. distance.

This same corner, U.S. Geological Survey Triangulation Station, "SEC COR 36/15S/11E", hereinbefore described.

N. 87°54.5' W., on the Third Standard Parallel South.

**2.72** Wash, 30 lks. wide, drains SW.

**2.840** The closing corner of sections 1 and 6, T. 16 S., Rs. 11 and 12 E., monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 8 ins. above ground, with the brass cap marked as described in the official record of the 1969 resurvey.

Continue on Third Standard Parallel South.

**23.400** Point for the E 1/16 section corner of section 1 only.

DEPENDENT RESURVEY OF A PORTION OF THE  
THIRD STANDARD PARALLEL SOUTH,  
T. 15 S., R. 11 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T15S R11E  
E 1/16 S1  
T16S  
1993

Set a 6 ft. steel fence post alongside the aluminum post.

**32.70** A dirt road, 44 lks. wide, bears N. 35° E. and S. 35° W.

**42.070** The standard 1/4 section corner of section 36 only, T. 15 S., R. 11 E., monumented with an iron post, 2 1/2 ins. diameter firmly set, projecting 10 ins. above ground, and in a collar of stone, with the brass cap marked as described in the official record of the 1969 resurvey.

---

S. 89°43.0' W., continue on the Third Standard Parallel South.

**1.885** The 1/4 section corner of section 1 only, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 6 ins. above ground, with a steel fence post alongside, and with the brass cap marked as described in the official record of the 1969 resurvey.

Raise a mound of stone, 4 ft. base, 2 ft. high, south of the corner.

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 16 S., R. 11 E., Salt Lake Meridian, Utah

---

Reestablishment of the Survey Executed by J.T. Breckon in 1895,  
and the Resurveys Executed by J.W. Dougall in 1913,  
and C.P. Sylvester in 1969

---

From the corner of sections 1, 6, 7, and 12, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 4 ins. above ground, and a mound of stone, 2 ft. base, 1 1/2 ft. high, west of corner, with the brass cap marked as described in the official record of the 1969 resurvey.

N. 0° 21.5' W., between sections 1 and 6.

**39.445** The 1/4 section corner of sections 1 and 6, on the east boundary of the township, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 8 ins. above ground, and a mound of stone to the west, with the brass cap marked as described in the official record of the 1969 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,  
T. 16 S., R. 11 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Due to the lotting of section 6, T. 16 S.R., 12 E., this corner is not a common 1/4 section corner for both sections. I therefore remove all marks pertaining to section 6, and add 1993 to the brass cap.

N. 1°15.5' W., beginning new measurement.

**0.256** Point for the 1/4 section corner of section 6 only, T. 16 S., R. 12 E.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T16S  
R11E R12E  
| 1/4  
S6  
1993

Raise a mound of stone, 3 ft. base, 1 ft. high, east of the corner.

**20.035** Point for the N 1/16 section corner of section 1 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T16S  
N 1/16 |  
S1 |  
R11E R12E  
1993

Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, east of the corner.

Corner falls on open rolling ground.

**38.760** The closing corner of sections 1 and 6, hereinbefore described.

---

The Subdivision of Section 1,  
T. 16 S., R. 11 E., Salt Lake Meridian, Utah

---

From the 1/4 section corner of sections 1 and 12, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 5 ins. above ground, with the brass cap marked as described in the official record of the 1969 resurvey.

The corner falls in river bottom area.

N. 0°34.0' W., on the N - S center line of section 1.

THE SUBDIVISION OF SECTION 1,  
T. 16 S., R. 11 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

12.00

Right bank of Price River, 50 lks. wide, drains E (scaled).

26.00

Left bank of Price River, 50 lks. wide, drains WSW (scaled).

39.800

Point for the center 1/4 section corner, at intersection with the E - W center line of section 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T16S R11E  
C 1/4 S1  
1993

Set a 6 ft. steel fence post alongside alongside the corner.

Corner falls in greasewood area in bottom lands of the Price River.

52.70

Right bank of Price River, 50 lks. wide, drains S. 40° E.

60.460

Point for the center N 1/16 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

C  
N 1/16 | S1  
C  
1993

Set a 6 ft. steel fence post alongside the corner.

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

This corner falls in a disturbed mining area.

79.670

The 1/4 section corner of section 1 only, on the north boundary of the township, hereinbefore described.

---

From the 1/4 section corner of section 1 only, on the east boundary of the township, hereinbefore described.

N. 89°35.0' W., on the E - W center line of section 1.

20.775

Point for the center E 1/16 section corner of section 1.

THE SUBDIVISION OF SECTION 1,  
T. 16 S., R. 11 E., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

C    $\frac{E \ 1/16}{S1}$    C  
1993

Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, north of the corner.

This corner falls at base of rocky hill in an open area.

**28.85**   Left bank of Price River, 50 lks. wide, drains south.

**41.550**   The center 1/4 section corner.

**62.020**   Point for the center W 1/16 section corner of section 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 20 ins. in the ground, set in a 3 1/2 ft. collar of stone, with aluminum cap marked:

C    $\frac{W \ 1/16}{S1}$    C  
1993

The corner falls on a flat bench area.

**82.490**   The 1/4 section corner of sections 1 and 2, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 5 ins. above ground, and in a mound of stone, with the brass cap marked as described in the official record of the 1969 resurvey.

---

From the center E 1/16 section corner of section 1.

N. 0°54.5' W., on the N - S center line of the NE 1/4 of section 1.

**20.345**   Point for the NE 1/16 section corner, at intersection with the E - W center line of the NE 1/4 of section 1.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diameter, 24 ins. in the ground, with aluminum cap marked:

T16S R11E  
NE 1/16   S1  
1993

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

THE SUBDIVISION OF SECTION 1,  
T. 16 S., R. 11 E., SALT LAKE MERIDIAN, UTAH

**CHAINS**

**39.350**

The E 1/16 section corner of section 1 only, on the north boundary of the township, hereinbefore described.

---

From the N 1/16 section corner of section 1 only, on the east boundary of the township, hereinbefore described.

N. 88°42.5' W., on the E - W center line of the NE 1/4 of section 1.

**20.660**

The NE 1/16 section corner.

**41.320**

The center N 1/16 section corner.

---

From the W 1/16 section corner of sections 1 and 12, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 8 ins. above ground, and in a collar of stone, with the brass cap marked as described in the official record of the 1969 resurvey.

N. 0°14.0' W., on the N - S center line of the SW 1/4 of section 1.

**39.980**

The center W 1/16 section corner.

---

N. 0°43.0' W., on the N - S center line of the NW 1/4 of section 1.

**27.00**

Right bank of Price River, 50 lks. wide, drains SE (scaled).

Continue in river.

**32.00**

Right bank of Price River, 50 lks. wide, drains S. 10° W. (scaled).

**35.45**

Right bank of Price River, 50 lks. wide, drains N. 75° E.

**39.685**

The W 1/16 section corner of section 1 only, on the north boundary of the township, monumented with an iron post, 2 1/2 ins. diameter, firmly set, projecting 3 ins. above ground, and a steel fence post alongside, with the brass cap marked as described in the official record of the 1969 resurvey.

Corner falls in bottom lands area of the Price River, in heavy brush and tamarisk.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

## FIELD ASSISTANTS

---

Name	Capacity
Shawn Peterson	Survey Technician
Jennifer Eames	Survey Technician
Shane Button	Survey Aid

## CERTIFICATE OF SURVEY

I, *Larry V. Judd, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *14th day of May, 1993*, I have *dependently resurveyed a portion of the Third Standard Parallel South; a portion of the east boundary, and subdivided section 1, in Township 16 South, Range 11 East,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 4, 1997

Date

*Larry V. Judd*  
(Cadastral Surveyor)

                      
Date

                      
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the Third Standard Parallel South, a portion of the east boundary, and the subdivision of section 1 in Township 16 South, Range 11 East, Salt Lake Meridian, Utah,*

executed by *Larry V. Judd, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

September 11, 1997

Date

*Daniel W. Webb*

(Chief Cadastral Surveyor for Utah)



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF

THE DEPENDENT RESURVEY OF

PORTIONS OF THE

NORTH, WEST (GUIDE MERIDIAN)

AND SOUTH BOUNDARIES,

AND A PORTION OF THE SUBDIVISIONAL LINES,

AND THE

SUBDIVISION OF SECTIONS 3, 6, 7, 10, 15, 18, 21, 28, AND 32

IN

TOWNSHIP 11 NORTH, RANGE 18 WEST

OF THE SALT LAKE MERIDIAN  
IN THE STATE OF UTAH

EXECUTED BY

*Gail E. Reynolds*  
*Cadastral Surveyor*

Under special instructions dated *May 12, 1993*, approved *May 12, 1993*, which provided for the surveys included under Group Number *805*, and assignment instructions dated *June 7, 1993*.

Survey commenced June 29, 1993

Survey completed September 22, 1993

## INDEX DIAGRAM

Township 11 North, Range 18 West

7	15	14	13	12		
	6 39	5 29	4 21	3 17	2	1
6	39 38	38	29 28	20	17	
6		28				
	7 37	8	9 19	10 16	11	12
5		27				
	37 36	36 35	27 26			
5	35					
	18	17	16	15	14	13
4	34	34	26			
	34	34	26			
4		26				
	19 33	20	21	22	23	24
3		25				
	33 32	32	25 24			
3	32	24				
	30	29	28 18	27	26	25
2	31	23				
		31 30	23 22			
	31	32	33	34	35	36
11	10	10	9	9	8	

The Subdivision of Section 3 .....	Page 40
The Subdivision of Section 6 .....	Page 41
The Subdivision of Section 7 .....	Page 43
The Subdivision of Section 10.....	Page 45
The Subdivision of Section 15.....	Page 48
The Subdivision of Section 18.....	Page 49
The Subdivision of Section 21.....	Page 50
The Subdivision of Section 28.....	Page 52
The Subdivision of Section 32.....	Page 54

## TOWNSHIP 11 NORTH, RANGE 18 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of portions of the north, west (Guide Meridian), and south boundaries and a portion of the subdivisional lines, and the survey of the subdivision of sections 3, 6, 7, 10, 15, 18, 21, 28, and 32, in Township 11 North, Range 18 West, Salt Lake Meridian, Utah.

**HISTORY OF EARLIER SURVEYS**

Surveyed by		<u>Retr. or Resurveyed by</u>	
NORTH BOUNDARY			
All	F. Dickert	1882	
SOUTH BOUNDARY			
All	F. Dickert	1882	
EAST BOUNDARY			
All	F. Dickert	1882	
WEST BOUNDARY (Guide Meridian)			
All	F. Dickert	1882	
SUBDIVISION			
All	H. Fitzhugh	1883	
Portion		C.P. Sylvester	1979
Portion		R.A. Zaninovich	1990

The survey was executed in accordance with the specifications set forth in the Manual of Surveying instructions, 1973, and the Special Instructions for Group No. 805, dated May 12, 1993.

The directions of the lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey and resurveys were retraced and a diligent search was made for any evidence of the original and resurvey field note records. Identified corners, when appropriate were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original or resurvey record. The retracement data were thoroughly verified and only the true line notes are given herein.

## TOWNSHIP 11 NORTH, RANGE 18 WEST, SALT LAKE MERIDIAN, UTAH

**CHAINS**

The geographic position of the corner of sections 27, 28, 33, and 34, as determined by a tie made to N.G.S. Triangulation Station "VT BM L 59" is as follows:

Latitude 41°38'21.39" N. Longitude 113°54'23.95" W.  
N.A.D. 1927

The mean magnetic declination as projected from the U.S. Geological Survey Magnetic Declination Map of 1990, is 15° E.

---

Dependent Resurvey of the West Boundary (Guide Meridian)  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by F. Dickert in 1882

---

From the corner of sections 25, 30, 31, and 36, at the corner of fences, projecting E, S, and W. This fence corner is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N	
R19W	R18W
S25	S30
S36	S31
1993	

Corner is located 40 lks. N of a wash, drains E in sagebrush.

N. 0°11.6' W., between sections 25 and 30.

Over rolling bench land, through sagebrush and widely scattered juniper.

**40.282**

Point for the 1/4 section corner of sections 25 and 30, at proportionate distance. There is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(GUIDE MERIDIAN)  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N  
R19W R18W  
1/4  
S25 | S30  
1993

Set a steel fence post alongside the aluminum post.

Corner is located on gently rolling land in sagebrush and widely scattered juniper growth.

Continue over rolling bench land and mountain land.

**80.564** The corner of sections 19, 24, 25, and 30, monumented with a trachyte stone, 30x30x24 ins., firmly set and dimly marked, with a mound of stone to the E.

At the corner point

Set an aluminum post, 30 ins. long, on solid rock and in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T11N  
R19W R18W  
S24 | S19  
S25 | S30  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located at base of a steep, N slope in sagebrush and juniper growth.

---

N. 0°21.8' W., between sections 19 and 24.

Over mountainous land, through juniper growth.

**39.348** The 1/4 section corner of sections 19 and 24, monumented with a trachyte stone, 24x24x18 ins., firmly set and dimly marked with a mound of stone to W, from which original bearing trees;

A juniper, 18 ins. diam., bears East, 30 lks. dist., with no visible marks.

A juniper, 36 ins. diam., bears West, 36 lks. dist., plainly marked  
1/4 S BT.

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(GUIDE MERIDIAN)  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock and in a mound of stone, 5 ft. base, to top of aluminum cap marked:

T11N  
R19W R18W  
1/4  
S24 | S19  
1993

Deposit a magnet alongside the aluminum post.

Deposit the marked stone alongside the aluminum post.

Corner is located on nearly level land in juniper.

N. 0°44.1' E., beginning new measurement.

Over mountainous land, through juniper growth.

**39.922** Point for the corner of sections 13, 18, 19, and 24, at proportionate distance. No remaining evidence of the original corner was found. Point falls in cultivated land and is not monumented.

N. 0°44.1' E., between sections 13 and 18.

Over rolling land, through cultivated land, sagebrush, and juniper growth.

**39.922** Point for the 1/4 section corner of sections 13 and 18, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T11N  
R19W R18W  
1/4  
S13 | S18  
1993

Set a steel fence post alongside the aluminum post.

Corner is located on nearly level cultivated land.

**59.883** Point for the N 1/16 section corner of sections 13 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(GUIDE MERIDIAN)  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N  
R19W R18W  
N 1/16  
S13 | S18  
1993

Set a steel fence post alongside the aluminum post.

Corner is located on gentle, S slope in sagebrush, 1.15 chains N of an improved gravel road bears SE and NW.

**79.844** The corner of sections 7, 12, 13, and 18, monumented with a mound of stone. This point is being utilized by local land owners and local surveyors as the section corner position, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 4 1/2 ft. base, to top of aluminum cap marked:

T11N  
R19W R18W  
S12 | S7  
S13 | S18  
1993

The corner is located on a SE slope in scattered juniper growth.

N. 0°04.4' E., between sections 7 and 12.

Over mountainous land, through juniper growth.

**40.806** The 1/4 section corner of sections 7 and 12, monumented with a 1/2 inch diam. rebar with a 2 inch diam., unmarked, aluminum cap. This monument is accepted as a careful and faithful reestablishment of the 1/4 section corner position.

No remaining evidence of the original 1/4 section corner was found.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 1/2 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(GUIDE MERIDIAN)  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N  
R19W R18W  
1/4  
S12 | S7  
1993

Set a steel fence post alongside the aluminum post.

Deposit the rebar and aluminum cap alongside the aluminum post.

The corner is located on a rocky, SW slope.

N. 0°04.4' E., beginning new measurement.

40.806

The corner of sections 1, 6, 7, and 12, monumented with a trachyte stone, 20x10x8 ins., firmly set and plainly marked with 1 notch on the N and 5 notches on the S edges, with mound of stone, 3 ft. base, by 1 1/2 ft. high to the E.

From which the original bearing tree and bearing object:

A granite boulder, 10x8x5 ft., bears North, 22 lks. dist., dimly marked.

A juniper, 12 ins. diam., bears N. 5° W., 42 lks. dist., plainly marked T11N R19W S1 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
R19W R18W  
S1 | S6  
S12 | S7  
1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on a W slope in juniper growth.

N. 0°03.9' E., between sections 1 and 6.

Over rolling mountain land, through sagebrush and juniper growth.

20.126

Point for the S 1/16 section corner of sections 1 and 6.



DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(GUIDE MERIDIAN)  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
R19W R18W  
S 1/16  
S1 | S6  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, NE slope in sagebrush and scattered juniper growth.

40.252

Point for the 1/4 section corner of sections 1 and 6, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N  
R19W R18W  
1/4  
S1 | S6  
1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, NE slope in sagebrush and juniper growth.

80.504

The corner of Townships 11 and 12 North, Ranges 18 and 19 West, monumented with a quartzite stone, 10x8x6 ins., firmly set and plainly marked with 6 notches on the N, E, S, and W edges.

From which the original bearing trees:

A juniper, 8 ins. diam., bears S. 60° E., 18 lks. dist., marked with a blaze and visible scribe marks.

A juniper, 8 ins. diam., bears S. 45° W., 50 lks. dist., marked with a blaze and visible scribe marks.

A juniper, 6 ins. diam., bears N. 88° W., 18 lks. dist., marked with a blaze and visible scribe marks.

At the corner point

DEPENDENT RESURVEY OF THE WEST BOUNDARY  
(GUIDE MERIDIAN)  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12N  
R19W R18W  
S36 | S31  
S1 | S6  
T11N  
R19W R18W  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located on a SW slope in juniper growth.

---

Dependent Resurvey of a Portion of the South Boundary,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by F. Dickert in 1882

---

From the corner of sections 3, 4, 33, and 34, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with the aluminum cap marked as described in the official record of the resurvey executed by R.A. Zaninovich in 1990.

S. 89°48.0' W., between sections 4 and 33.

Over gently rolling land, through cultivated fields.

**20.137** Point for the E 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
E 1/16 S33  
S4  
T10N R18W  
1993

Deposit a magnet alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.274

Point for the 1/4 section corner of sections 4 and 33, at proportionate distance. No remaining evidence of the original corner was found. Not monumented due to private land ownership.

80.548

Point for the corner of sections 4, 5, 32, and 33, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W	
<u>S32</u>	<u>S33</u>
S5	S4
T10N R18W	
1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

---

S. 89°48.0' W., between sections 5 and 32.

Over gently rolling benchland, through sagebrush and native grasses.

20.137

Point for the E 1/16 section corner of sections 5 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T11N R18W	
E 1/16	<u>S32</u>
	S5
T10N R18W	
1993	

Set a steel fence post alongside the aluminum post.

The corner is located in the center of an old trail road, bears E and W, in sagebrush.

40.274

Point for the 1/4 section corner of sections 5 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W  
1/4  $\frac{S32}{S5}$   
T10N R18W  
1993

The corner is located on nearly level ground in sagebrush.

80.548

Point for the corner of sections 5, 6, 31, and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
 $\frac{S31}{S6}$  |  $\frac{S32}{S5}$   
T10N R18W  
1993

Deposit a magnet alongside the aluminum post.

The corner is located 18 lks. dist. N of a steel gate in a 4 strand barbed-wire fence line, bears E and W on nearly level ground in sagebrush.

---

S. 89°48.0' W., between sections 6 and 31.

Over gently rolling land, through sagebrush and native grasses.

40.274

Point for the 1/4 section corner of sections 6 and 31, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  $\frac{S31}{S6}$   
T10N R18W  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 14 lks. dist. N of a 4 strand barbed-wire fence line, bears E and W, on nearly level land in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS  
79.743

The corner of Townships 10 and 11 North, Ranges 18 and 19 West, monumented with a dimly marked granite stone, 18x16x12 ins., firmly set in a 4 strand barbed-wire fence corner, bears N, S, E, and W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N
R19W R18W
<u>S36</u>   <u>S31</u>
S1   S6
T10N
R19W R18W
1993

Deposit the marked stone alongside the aluminum post.

Deposit a magnet alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

---

Dependent Resurvey of a Portion of the North Boundary,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

Reestablishment of the Survey Executed by F. Dickert in 1882

---

From the corner of sections 2, 3, 34, and 35, Townships 11 and 12 North, Range 18 West, monumented with a granite stone, 10x6x5 ins., firmly set, and plainly marked with 2 notches on E and 4 notches on W edges.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12N R18W
<u>S34</u>   <u>S35</u>
S3   S2
T11N R18W
1993

Deposit the marked stone alongside the aluminum post.

The corner is located on a SW slope in a 4 strand barbed-wire fence corner, bears E, S and W, in sagebrush and juniper growth.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

S. 89°30.7' W., between sections 3 and 34.

Over rolling mountain land, through sagebrush and juniper growth.

**40.184** The 1/4 section corner of sections 3 and 34, at the corner of fences, projecting N, E and W.  
This point is accepted as the best available evidence of the position of the original corner

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

	T12N R18W
1/4	<u>S34</u>
	S3
	T11N R18W
	1993

The corner is located on a gentle, S slope in juniper growth.

---

S. 89°32.2' W., beginning new measurement.

**40.070** The corner of sections 3, 4, 33, and 34, monumented with a conglomerate stone, 16x12x3 ins., firmly set, and plainly marked with 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

	T12N R18W
	<u>S33</u>   <u>S34</u>
	S4   S3
	T11N R18W
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a rolling S slope in a 4 strand barbed-wire fence corner, bears N, S and W., and with an old abandoned fence to the E, in sagebrush and juniper growth.

---

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 89°51.7' W., between sections 4 and 33.

Over rolling mountain land, through sagebrush and juniper growth.

**19.950** Point for the E 1/16 section corner of sections 4 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N R18W  
E 1/16  $\frac{S33}{S4}$   
T11N R18W  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gentle rolling ground, 8 lks. N of a 4 strand barbed-wire fence line, bears E and W, in dense juniper growth.

**39.900** The 1/4 section corner of sections 4 and 33, monumented with a conglomerate stone, 10x8x8 ins., firmly set and plainly marked 1/4 on top of stone.

The original juniper bearing tree was found laying over and dead at record bearing and distance.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T12N R18W  
1/4  $\frac{S33}{S4}$   
T11N R18W  
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located on a gentle S slope in juniper growth.

S. 89°57.0' W., beginning new measurement.

**40.108** The corner of sections 4, 5, 32, and 33, monumented with a quartzite stone, 18x8x4 ins., firmly set, and plainly marked with 4 notches on E and 2 notches on W edges.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N	R18W
<u>S32</u>	<u>S33</u>
S5	S4
T11N	R18W
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling, SE slope in sagebrush and scattered juniper growth.

---

N. 89°39.8' W., between sections 5 and 32.

Over rolling mountain land, through sagebrush and juniper growth.

39.948

Point for the 1/4 section corner of sections 5 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T12N	R18W
	<u>1/4</u>	<u>S32</u>
		S5
	T11N	R18W
	1993	

Raise a mound of stone N of the corner.

The corner is located on a gentle, E slope in native grasses, sagebrush and scattered juniper growth.

79.896

Point for the corner of sections 5, 6, 31, and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T12N R18W  
S31 | S32  
S6 | S5  
T11N R18W  
1993

The corner is located on nearly level land in native grasses, sagebrush and scattered juniper growth.

N. 89°39.8' W., between sections 6 and 31.

Over rolling mountain land, through sagebrush and juniper growth.

**39.948** Point for the 1/4 section corner of sections 6 and 31, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T12N R18W  
1/4    S31  
         S6  
T11N R18W  
1993

Raise a mound of stone N of the corner.

The corner is located on a NW slope in juniper growth.

**59.922** Point for the W 1/16 section corner of sections 6 and 31.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T12N R18W  
W 1/16    S31  
             S6  
T11N R18W  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling NW slope in sagebrush and juniper growth.

**79.197** The corner of Townships 11 and 12 North, Ranges 18 and 19 West, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by H. Fitzhugh in 1883.

From the corner of sections 10, 11, 14, and 15, monumented with an aluminum post, 2 1/2 ins. in diam., extending 6 ins. out of the ground, with the aluminum cap marked as described in the official record of the resurvey by C. P. Sylvester in 1979.

N. 0°15.4' W., between sections 10 and 11.

Over pasture land.

40.064

Point for the 1/4 section corner of sections 10 and 11, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W	
1/4	
S10	S11
1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

80.128

Point for the corner of sections 2, 3, 10, and 11, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T11N R18W	
S3	S2
S10	S11
1993	

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

From the 1/4 section corner of sections 2 and 11, monumented with a quartzite stone, 16x12x4 ins., firmly set, and plainly marked 1/4 on the N face.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S2  
         S11  
         1993

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed-wire fence line, bears E and W, on rolling W slope in sagebrush.

N. 89°12.1' W., between sections 2 and 11.

Over gently rolling, W slope, through sagebrush and pasture land.

40.005

The corner of sections 2, 3, 10 and 11.

---

N. 0°21.9' E., between sections 2 and 3.

Over nearly level pasture land.

40.064

Point for the 1/4 section corner of sections 2 and 3, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S3 | S2  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

Continue over pasture land and the residential area of Grouse Creek, Utah.

80.828

The corner of sections 2, 3, 34, and 35, on north boundary of the township, hereinbefore described.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Reestablishment of the Survey Executed by H. Fitzhugh in 1883  
and the Dependent Resurvey Executed by R. A. Zaninovich in 1990.

From the corner of sections 27, 28, 33, and 34, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with aluminum cap, marked as described in the official record of the resurvey by R. A. Zaninovich in 1990.

From this corner:

National Geodetic Survey triangulation station "VT BM L59" bears N. 45°46.7' E., 55.627 chains distance.

N. 0°08.8' W., between sections 27 and 28.

Over gently rolling cultivated land.

**41.058** Point for the 1/4 section corner of sections 27 and 28, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S28 | S27  
1993

Deposit a magnet alongside aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

**82.116** The corner of sections 21, 22, 27, and 28, monumented with an aluminum post, projecting 8 ins. out of a collar of stone, with aluminum cap marked as described in the official record of the resurvey by C. P. Sylvester in 1979.

Reestablishment of the Survey Executed by H. Fitzhugh in 1883

From the corner of sections 9, 10, 15, and 16, monumented with an aluminum post, 2 1/2 ins. diam., projecting 9 ins. out of a collar of stone, with aluminum cap marked as described in the official record of the 1979 resurvey by C.P. Sylvester.

N. 0°12.7' W., between sections 9 and 10.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Over gently rolling bench land, through sagebrush and widely scattered juniper.

**39.876** Point for the 1/4 section corner of sections 9 and 10, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S9 | S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling E slope in sagebrush and widely scattered juniper growth.

**59.814** Point for the N 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
N 1/16  
S9 | S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle S, slope in sagebrush.

**79.752** The corner of sections 3, 4, 9, and 10, monumented with a quartzite stone, 18x12x3 ins., firmly set, and plainly marked with 3 notches on E and 5 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
S4 | S3  
S9 | S10  
1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling S slope in sagebrush and scattered juniper growth.

From the corner of sections 2, 3, 10, and 11.

S. 89°47.7' W., between sections 3 and 10.

Over pasture land and rolling bench land.

39.846

The 1/4 section corner of sections 3 and 10, monumented with a quartzite stone, 14x9x4 ins., firmly set and plainly marked 1/4 on N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
1/4	<u>S3</u>
	S10
	1993

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed wire fence line, bears N and S in sagebrush to E and pasture to the W.

S. 89°32.6' W., beginning new measurement.

Over rolling bench land, through pasture land.

20.186

Point for the W 1/16 section corner of sections 3 and 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
W 1/16	<u>S3</u>
	S10
	1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level, dry, pasture land on the N edge of an old abandoned road, bears NE and SW.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.372

The corner of sections 3, 4, 9, and 10.

---

N. 0°19.6' E., between sections 3 and 4.

Over rolling bench land, through sagebrush and juniper growth.

40.064

Point for the 1/4 section corner of sections 3 and 4, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S4 | S3  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush, native grasses, and scattered juniper growth.

60.096

Point for the N 1/16 section corner of sections 3 and 4.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
N 1/16  
S4 | S3  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush.

80.629

The corner of sections 3, 4, 33, and 34 on the north boundary of the township, hereinbefore described.

---

From the corner of sections 4, 5, 32, and 33, on the south boundary of the township, hereinbefore described.

N. 0°05.6' W., between sections 32 and 33.

Over cultivated land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.018

Point for the 1/4 section corner of sections 32 and 33, at proportionate distance. No remaining evidence of the original corner was found.

Point falls in cultivated land and is not monumented.

80.036

Point for the corner of sections 28, 29, 32, and 33, at proportionate distance. No remaining evidence of the original corner was found.

Point falls in cultivated land and is not monumented.

From the corner of sections 27, 28, 33, and 34

S. 89°44.4' W., between sections 28 and 33.

Over rolling cultivated land.

20.093

Point for the E 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
E 1/16	<u>S28</u>
	S33
	1993

Set a steel fence post alongside the aluminum post.

The corner is located 2 lks. S of a 4 strand barbed-wire fence line, bears E and W, with cultivated land on the S side of the fence and sagebrush on the N.

40.186

Point for the 1/4 section corner of sections 28 and 33, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
1/4	<u>S28</u>
	S33
	1993

Set a steel fence post alongside the aluminum post.

The corner is located 2 1/2 lks. S of a 4 strand barbed-wire fence line, bears E and W, in sagebrush.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

60.279

Point for the W 1/16 section corner of sections 28 and 33.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
	<u>S28</u>
W 1/16	S33
	1993

Set a steel fence post alongside the aluminum post.

Deposit a magnet alongside the aluminum post.

The corner is located on gently rolling land in sagebrush.

80.372

The point for the corner of sections 28, 29, 32, and 33.

N. 0°54.6' E., between sections 28 and 29.

Over gently rolling cultivated land.

20.012

Point for the S 1/16 section corner of sections 28 and 29.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
	S 1/16
S29	S28
	1993

Deposit a magnet alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level pasture land.

40.024

The 1/4 section corner of sections 28 and 29, monumented with a quartzite stone, 14x10x6 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W

1/4

S29 | S28

1993

From which

The SW corner of an old cemetery, bears N. 2° 36' E., 5.24 chs. dist.

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling, SE slope in sagebrush.

N. 0°19.8' W., beginning new measurement.

39.716

The corner of sections 20, 21, 28, and 29, monumented with a quartzite stone, 18x10x4 ins., firmly set at a fence corner and plainly marked with 2 notches on S and 4 notches on E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

S20 | S21

S29 | S28

1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located in a 4 strand barbwire fence corner, bears E and S.

From the corner of sections 21, 22, 27, and 28.

S. 88°01.6' W., between sections 21 and 28.

Over rolling bench land, through sagebrush and scattered juniper growth.

39.892

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance. No remaining evidence of the original corner was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T11N R18W  
1/4    S21  
         S28  
         1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, S slope in sagebrush and widely scattered juniper growth.

59.838

Point for the W 1/16 section corner of sections 21 and 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
W 1/16    S21  
             S28  
             1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle W slope, 20 lks. N of a fence line, 4 strand barbed wire, bears E and W, in sagebrush and widely scattered juniper growth.

79.784

The corner of sections 20, 21, 28, and 29.

---

N. 0°27.8' W., between sections 20 and 21.

Over rolling bench land, through sagebrush and widely scattered juniper growth.

39.876

Point for the 1/4 section corner of sections 20 and 21, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

T11N R18W  
         1/4  
S20 | S21  
         1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cleared land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

79.752

The corner of sections 16, 17, 20, and 21, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with aluminum cap, marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

The corner is located on nearly level land in a 4 strand barbed-wire fence corner, bears N and E.

---

Reestablishment of the Survey Executed by H. Fitzhugh in 1883 and  
the Resurvey Executed by Craig P. Sylvester in 1979

---

From the 1/4 section corner of sections 16 and 21, monumented with an aluminum post, 2 1/2 ins. in diam. projecting 6 ins. above the ground, with aluminum cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

S. 89°15.8' W., between sections 16 and 21.

Over rolling bench land, through sagebrush.

19.958

Point for the W 1/16 section corner of sections 16 and 21.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
W 1/16	<u>S16</u>
	S21
	1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling land in sagebrush, 17 lks. N of a 4 strand barbed wire fence line, bears E and W.

39.916

The corner of sections 16, 17, 20, and 21.

---

Reestablishment of the Survey Executed by H. Fitzhugh in 1883.

---

From the corner of sections 9, 10, 15, and 16.

S. 89°22.3' W., between sections 9 and 16.

Over rolling bench land, through sagebrush and scattered juniper.

39.691

Point for the 1/4 section corner of sections 9 and 16, at proportionate distance. No remaining evidence of the original corner was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
1/4	<u>S9</u>
	S16
	1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush and scattered juniper.

79.382

Point for the corner of sections 8, 9, 16, and 17, at proportionate distance. No remaining evidence of the original corner was found.

The point falls in an improved gravel road, bears NE and SW. Set a spike flush with the road surface.

From which I set:

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears S. 45° E., .758 chs. dist., with aluminum cap, marked: T11N R18W S16 N 45 W 50 FT. 1993.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears S. 45° W., .758 chs. dist., with aluminum cap marked: T11N R18W S17 N 45 E 50 ft. 1993

Set steel fence posts alongside the aluminum posts.

From this corner, the corner of sections 16, 17, 20 and 21, bears S. 0°32.3' E., 79.914 chains distance. The intervening 1/4 section corner was not found.

N. 0°14.7' W., between sections 8 and 9.

Over rolling bench land, through sagebrush and scattered juniper.

39.956

Point for the 1/4 section corner of sections 8 and 9, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W

1/4

S8 | S9

1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

79.912

The corner of sections 4, 5, 8, and 9, monumented with a limestone, 18x15x10 ins., firmly set, and plainly marked with 4 notches on E and 5 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T11N R18W

S5 | S4

S8 | S9

1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a gentle, SE slope in juniper growth.

From the corner of sections 3, 4, 9, and 10.

S. 89°29.1' W., between sections 4 and 9.

Over rolling bench land, through sagebrush and juniper growth.

39.704

Point for the 1/4 section corner of sections 4 and 9, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

1/4    S4

S9

1993

The corner is located on nearly level ground in sagebrush and native grasses.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

79.408

The corner of sections 4, 5, 8, and 9.

N. 0°06.8' W., between sections 4 and 5.

Over rolling bench land, through sagebrush and juniper growth.

40.198

Point for the 1/4 section corner of sections 4 and 5, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S5 | S4  
1993

Raise a mound of stone W of the corner.

The corner is located on a low ridge, bears SE and NW, in juniper growth.

81.401

The corner of sections 4, 5, 32, and 33, on the north boundary of the township, hereinbefore described.

From the corner of sections 5, 6, 31, and 32, on the south boundary of the township, hereinbefore described.

N. 0°04.3' W., between sections 31 and 32.

Over gently rolling bench land, through sagebrush and native grasses.

39.918

Point for the 1/4 section corner of sections 31 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S31 | S32  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush and native grasses.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

79.836

Point for the section corner of sections 29, 30, 31, and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N	R18W
S30	S29
S31	S32
1993	

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a S slope in sagebrush, 17 lks. S of a 4 strand barbed-wire fence line, bears E and W.

---

From the point for the corner of sections 28, 29, 32, and 33.

S. 89°39.5' W., between sections 29 and 32.

Over rolling cultivated land.

20.126

Point for the E 1/16 section corner of sections 29 and 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground, with aluminum cap marked:

	T11N	R18W
E 1/16		S29
		S32
		1993

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level cultivated land.

40.252

Point for the 1/4 section corner of sections 29 and 32, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W

1/4 S29  
S32  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush and native grasses.

80.504

The corner of sections 29, 30, 31, and 32.

N. 89°45.6' W., between sections 30 and 31.

Over rolling bench land, through sagebrush and scattered juniper growth.

40.086

Point for the 1/4 section corner of sections 30 and 31, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

1/4 S30  
S31  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 17 lks. N of a 4 strand barbed wire fence line, bears E and W, on gentle, S slope in sagebrush and scattered juniper growth.

80.472

The corner of sections 25, 30, 31, and 36, on the west boundary of the township, hereinbefore described.

From the corner of sections 29, 30, 31, and 32.

N. 0°04.0' W., between sections 29 and 30.

Over rolling bench land, through sagebrush and native grasses.

39.918

Point for the 1/4 section corner of sections 29 and 30, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W

1/4

S30 | S29

1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level ground in sagebrush.

79.836

Point for the corner of sections 19, 20, 29, and 30, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

S19 | S20

S30 | S29

1993

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, E slope in sagebrush.

---

From the corner of sections 20, 21, 28, and 29.

S. 89°44.0' W., between sections 20 and 29.

Over rolling bench land, through sagebrush and cultivated land.

40.492

Point for the 1/4 section corner of sections 20 and 29, at proportionate distance. No remaining evidence of the original corner was found. Point falls on cultivated land and is not monumented.

80.984

The corner of sections 19, 20, 29, and 30.

---

N. 89°14.7' W., between sections 19 and 30.

Over rolling bench land, through sagebrush.

40.268

Point for the 1/4 section corner of sections 19 and 30, at proportionate distance. No remaining evidence of the original corner was found.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S19  
         S30  
         1993

Raise a mound of stone N of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, SE slope, in sagebrush and scattered juniper growth.

80.636

The corner of sections 19, 24, 25, and 30, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 19, 20, 29, and 30.

N. 0°04.7' E., between sections 19 and 20.

Over rolling bench land, through sagebrush and scattered juniper growth.

39.918

Point for the 1/4 section corner of sections 19 and 20, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
         1/4  
S19 | S20  
         1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, N slope in sagebrush and scattered juniper growth.

Continue over benchland and cultivated land.

79.836

Point for the corner of sections 17, 18, 19, and 20, at proportionate distance. No remaining evidence of the original corner was found.

Corner falls in cultivated land and is not monumented.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the corner of sections 16, 17, 20, and 21.

S. 89°47.5' W., between sections 17 and 20.

Over cultivated and broken bench land, through pasture and juniper growth.

**40.106** Point for the 1/4 section corner of sections 17 and 20, at proportionate distance. No remaining evidence of the original corner was found.

Corner falls in cultivated land and is not monumented.

**80.212** The point for the corner of sections 17, 18, 19, and 20, not monumented.

N. 89°39.0' W., between sections 18 and 19.

Over cultivated and broken bench land, through pasture, sagebrush, and juniper growth.

**40.116** Point for the 1/4 section corner of sections 18 and 19, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a collar of stone, with aluminum cap marked:

T11N R18W  
1/4    S18  
         S19  
         1993

The corner is located on a S slope in juniper growth.

**80.462** The point for the corner of sections 13, 18, 19, and 24 on the west boundary of the township, hereinbefore described.

From the point for the corner of sections 17, 18, 19, and 20.

N. 0°04.9' E., between sections 17 and 18.

Over gently rolling pasture land.

**39.918** The 1/4 section corner of sections 17 and 18, monumented with a quartzite stone, 14x8x5 ins., firmly set and plainly marked 1/4 on the W face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4  
S18 | S17  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed wire fence corner, bears N, E and W, on nearly level cultivated land.

N. 0°42.2' W., beginning new measurement.

40.029

The corner of sections 7, 8, 17, and 18, monumented with a quartzite stone, 18x9x4 ins., firmly set, and plainly marked with 5 notches on E and 4 notches on S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
S7 | S8  
S18 | S17  
1993

Deposit the marked stone alongside the aluminum post.

The corner is located in a 4 strand barbed wire fence corner, bears E, S and W, on nearly level land in sagebrush and scattered juniper growth.

From the corner of sections 8, 9, 16, and 17.

S. 89°48.9' W., between sections 8 and 17.

Over rolling bench land, cultivated land and broken bench land, through sagebrush, pasture and scattered juniper

39.938

Point for the 1/4 section corner of sections 8 and 17, at proportionate distance. The original corner a quartzite, 19x6x5 ins., plainly marked was found lying loose on the ground, (May have been disturbed by a bulldozer at one time).

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W

1/4    S8  
      S17  
      1993

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush and native grasses.

79.876 The corner of sections 7, 8, 17, and 18.

N. 89°43.3' W., between sections 7 and 18.

19.746 Point for the E 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

E 1/16    S7  
          S18  
          1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, W slope in sagebrush and scattered juniper growth.

39.492 Point for the 1/4 section corner of sections 7 and 18, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W

1/4    S7  
      S18  
      1993

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on the W edge of a field, bears NW and SE.

Continue over broken bench land.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

78.984

The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0°07.3' W., between sections 7 and 8.

Over rolling bench land, through sagebrush and scattered juniper growth.

40.040

Point for the 1/4 section corner of sections 7 and 8, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post 30 ins. long, 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N R18W	
1/4	
S7	S8
1993	

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in sagebrush.

80.080

The corner of sections 5, 6, 7, and 8, monumented with a quartzite stone, 20x8x8 ins. firmly set and plainly marked with 5 notches on the E and S edges.

At the corner point

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N R18W	
S6	S5
S7	S8
1993	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone W of the corner.

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, W slope in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the corner of sections 4, 5, 8, and 9.

N. 89°57.0' W., between sections 5 and 8.

Over rolling bench land through sagebrush and juniper growth.

39.702

The 1/4 section corner of sections 5 and 8, monumented with a conglomerate stone, 22x10x8 ins., firmly set and dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S5  
         S8  
         1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

The corner is located 20 lks. W of a draw, drains S, in sagebrush.

S. 89°48.4' W., beginning new measurement.

39.986

The corner of sections 5, 6, 7, and 8.

N. 88°36.2' W., between sections 6 and 7.

Over rolling bench land, through sagebrush and scattered juniper growth.

39.754

Point for the 1/4 section corner of sections 6 and 7, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
1/4    S6  
         S7  
         1993

Raise a mound of stone N of the corner.

The corner is located on nearly level land in sagebrush and native grasses.



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 11 S., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

59.631

Point for the W 1/16 section corner of sections 6 and 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
W 1/16	<u>S6</u>
	S7
	1993

Set a steel fence post alongside the aluminum post.

The corner is located 29 lks. S of a 4 strand barbed-wire fence line, bears E and W, on E slope in sagebrush.

Continue over broken mountain land, through sagebrush and juniper growth.

78.713

The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

---

From the corner of sections 5, 6, 7, and 8.

N. 0°16.2' W., between sections 5 and 6.

Over rolling bench land, through sagebrush and juniper growth.

40.660

Point for the 1/4 section corner of sections 5 and 6, at proportionate distance. No remaining evidence of the original corner was found.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T11N R18W
	1/4
S6	S5
	1993

Raise a mound of stone W of the corner.

The corner is located on a S slope at the base of a small hill in sagebrush and scattered juniper growth.

81.970

The corner of sections 5, 6, 31, and 32, on the north boundary of the township, hereinbefore described.

---

THE SUBDIVISION OF SECTION 3,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The Subdivision of Section 3,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

From the 1/4 section corner of section 3 and 10.

N. 0°07.2' E., on the N - S center line of section 3.

39.977

Point for the center 1/4 section corner, at intersection with the E - W center line of section 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4  
S3  
1993

Deposit a magnet at the base of the aluminum post.

Set a steel fence post alongside the aluminum post.

The corner is located S. 1°37' W., 29 lks. dist., of a fence corner bears N and W.

60.003

Point for the center N 1/16 section corner of section 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  
N 1/16 | S3  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located N. 1°38' E., 95 lks dist., of a 4 strand barbed-wire fence corner, bears E, S, and W.

80.629

The 1/4 section corner of sections 3 and 34, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 2 and 3.

S. 89°40.0' W., on the E - W center line of section 3.

THE SUBDIVISION OF SECTION 3,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

40.014

The center 1/4 section corner of section 3.

60.125

Point for the center W 1/16 section corner of section 3.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap marked:

T11N R18W  
C — W 1/16 — C  
S3  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 31 1/2 lks. E of a 4 strand barbed wire fence line, bears N and S.

80.236

The 1/4 section corner of sections 3 and 4.

---

From the W 1/16 section corner of sections 3 and 10.

N. 0°13.4' E., on the N - S center line of the SW 1/4 of section 3.

40.020

The center W 1/16 corner of section 3.

---

From the center N 1/16 section corner of section 3.

S. 89°40.3' W., on the E - W center line of the NW 1/4 of section 3.

40.146

The N 1/16 section corner of sections 3 and 4.

---

The Subdivision of Section 6,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 6 and 7.

N. 0°25.3' W., on the N - S center line of section 6.

20.230

Point for the center S 1/16 section corner of section 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 6,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W  
C  
S 1/16 | S6  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 6 1/2 lks. W of a 4 strand barbed wire fence line, bears N and S, on SW slope in dense juniper growth.

**40.460** Point for the center 1/4 section corner, at intersection with the E - W center line of section 6.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S6  
1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located in the bottom of a draw, drains SW, in juniper growth.

**81.234** The 1/4 section corner of sections 6 and 31, on the north boundary of the township, hereinbefore described.

From the 1/4 section corner of sections 5 and 6.

N. 88°53.8' W., on the E - W center line of section 6.

**39.852** The center 1/4 section corner of section 6.

**51.778** Point selected for the witness corner to the center W 1/16 section corner section 6. The true point falls within a reservoir and cannot be monumented.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

WC  
T11N R18W  
C — W 1/16 — C  
S6  
1993

THE SUBDIVISION OF SECTION 6,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set a steel fence post alongside the aluminum post.

The corner is located in an old, trail road, bears N and S, on gentle, W slope in sagebrush.

**59.778** True point for the center W 1/16 section corner of section 6.

**78.459** The 1/4 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

---

From the W 1/16 section corner of sections 6 and 7.

N. 0°29.9' W. on the N - S center line of the SW 1/4 of section 6.

**20.180** Point for the SW 1/16 section corner, at intersection with the E - W center line of the SW 1/4 of section 6. Point falls in reservoir and is not monumented.

**40.359** True point for the center W 1/16 section corner of section 6.

---

From the center S 1/16 section corner of section 6.

N. 88°45.2' W. on the E - W center line of the SW 1/4 of section 6.

**19.902** The point for the SW 1/16 section corner of section 6.

**38.784** The S 1/16 section corner of sections 1 and 6, on the west boundary of the township, hereinbefore described.

---

From the true point for the center W 1/16 section corner of section 6.

N. 0°30.0' W. on the N - S center line of the NW 1/4 of section 6.

**40.506** The W 1/16 section corner of sections 6 and 31, on the north boundary of the township, hereinbefore described.

---

The Subdivision of Section 7,  
T. 11 N. R. 18 W. Salt Lake Meridian Utah.

---

From the 1/4 section corner of sections 7 and 18.

N. 0°18.3' W. on the N - S center line of section 7.

THE SUBDIVISION OF SECTION 7,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

33.426

Point for an Angle Point of private property corner.

Set an aluminum post 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

AP  
T11N R18W  
C  
S7 |  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 6 lks. N of a 4 strand barbed-wire fence line, bears E and W, irregularly on nearly level lands in sagebrush and cottonwood trees.

40.426

Point for the center 1/4 section corner at intersection with the E - W center line.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground, with an aluminum cap marked:

T11N R18W  
C 1/4 S7  
1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone W of the corner.

The corner is located on a SE slope in sagebrush and juniper growth.

80.856

The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

N. 89°09.8' W., on the E - W center line of section 7.

19.811

Point for the center E 1/16 section corner of section 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C — E 1/16 — C  
S7  
1993

THE SUBDIVISION OF SECTION 7,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The corner is located on gently rolling land in sagebrush and scattered juniper growth.

**39.622** The center 1/4 section corner of section 7.

**78.846** The 1/4 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

---

From the E 1/16 section corner of sections 7 and 18.

N. 0°12.8' W., on the N - S center line of the SE 1/4 of section 7.

**33.233** Point for an Angle Point of private property corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

AP  
T11N R18W  
S7

1993

Set a steel fence post alongside the aluminum post.

The corner is located on a SW slope in sagebrush and scattered juniper growth.

From this corner, the Angle Point on the N - S center line of the section, bears N. 89°09.6' W., 19.800 chains distance.

**40.233** The center E 1/16 section corner of section 7.

---

The Subdivision of Section 10,  
T 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 10 and 15, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground and in a collar of stone, with the aluminum cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

N. 1°01.8' W., on the N - S center line of section 10.

**39.006** Point for the center 1/4 section corner, at intersection with the E - W center line of section 10.

THE SUBDIVISION OF SECTION 10,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

**CHAINS**

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a E slope in juniper.

**59.037** Point for the center N 1/16 section corner of section 10; not monumented.

**79.068** The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of sections 10 and 11.

S. 89°48.2' W., on the E - W center line of section 10.

**39.316** The center 1/4 section corner of section 10.

**49.551** Point for the center E - W 1/64 section corner of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T11N R18W  
C  $\frac{E-W \ 1/64}{S10}$  C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located in a dump site area, 50 lks. E of the N end of the pit, bears SW.

**59.786** Point for the center W 1/16 section corner of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  $\frac{W \ 1/16}{S10}$  C  
1993

Set a steel fence post alongside the aluminum post.



THE SUBDIVISION OF SECTION 10,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The corner is located on a NW slope in sagebrush.

80.256

The 1/4 section corner of sections 9 and 10.

From the center W 1/16 section corner of section 10.

N. 0°37.1' W., on the N - S center line of the NW 1/4 of section 10.

19.984

Point for the NW 1/16 section corner, at intersection with the E - W center line of the NW 1/4 of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
NW 1/16 S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 7 lks. N of a 4 strand barbed-wire fence line, bears E and W, on nearly level dry pasture.

39.968

The W 1/16 section corner of sections 3 and 10.

From the point for the center N 1/16 section corner of section 10.

S. 89°40.3' W., on the E - W center line of the NW 1/4 of section 10.

10.164

Point for the center E - NW 1/64 section corner of section 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C E NW 1/64 S10  
1993

Set a steel fence post alongside the aluminum post.

The corner is located 2 lks. N of a 4 strand barbed-wire fence line, bears E and W on gentle, SW slope in dry pasture.

20.328

The NW 1/16 section corner of section 10.

40.656

The N 1/16 section corner of sections 9 and 10.

THE SUBDIVISION OF SECTION 10,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center E - W 1/64 section corner of section 10.

N. 0°49.3' W., on the N - S center line of the SE 1/4 of the NW 1/4 of section 10.

20.007

The center E - NW 1/64 section corner of section 10.

---

The Subdivision of Section 15,  
T. 11 N. R. 18 W. Salt Lake Meridian Utah

---

From the 1/4 section corner of sections 15 and 22, monumented with an aluminum post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with aluminum cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

N. 0°25.7' E., on the N - S center line of section 15.

38.411

Point for the center 1/4 section corner at intersection with the E - W center line of section 15.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N R18W  
C 1/4 S15  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling land in sagebrush.

79.496

The 1/4 section corner of sections 10 and 15.

---

From the 1/4 section corner of sections 14 and 15.

N. 89°43.5' W., on the E - W center line of section 15.

38.807

The center 1/4 section corner of section 15.

59.597

Point for the center W 1/16 section corner of section 15.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

THE SUBDIVISION OF SECTION 15,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W  
C —  $\frac{W \ 1/16}{S15}$  — C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle E slope in sagebrush.

- 80.387** The 1/4 section corner of sections 15 and 16, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, and in a collar of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

From the W 1/16 section corner of sections 15 and 22, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, and in a collar of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

N. 0°56.7' W., on the N - S center line of the SW 1/4 of section 15.

- 39.162** The center W 1/16 section corner of section 15.

N. 0°29.7' E., on the N - S center line of the NW 1/4 of section 15.

- 40.468** The W 1/16 section corner of sections 10 and 15, monumented with an iron post, 2 1/2 ins. diam., projecting 6 ins. out of the ground, with brass cap, marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

The Subdivision of Section 18,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 18 and 19.

N. 0°07.7' E., on the N - S center line of section 18.

- 39.921** Point for the center 1/4 section corner, at intersection with the E - W center line of section 18.

Set an aluminum post, 30 ins. Long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 18,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

T11N R18W  
C 1/4 S18  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on the W edge of an improved gravel road, bears N and S.

**59.906** Point for the center N 1/16 section corner of section 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  
N 1/16 | S18  
C  
1993

Set a steel fence post alongside the aluminum post.

**79.891** The 1/4 section corner of sections 7 and 18.

---

From the 1/4 section corner of sections 17 and 18.

N. 89°38.7' W., on the E - W center line of section 18.

**40.078** The center 1/4 section corner of section 18.

**79.997** The 1/4 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

---

From the center N 1/16 section corner of section 18.

N. 89°41.1' W., on the E - W center line of the NW 1/4 of section 18.

**39.706** The N 1/16 section corner of sections 13 and 18, on the west boundary of the township, hereinbefore described.

---

The Subdivision of Section 21,  
T 11 N., R. 18 W., Salt Lake Meridian Utah

---

From the 1/4 section corner of sections 21 and 28.

THE SUBDIVISION OF SECTION 21,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

N. 0°25.8' W., on the N - S center line of section 21.

**39.034** Point for the center 1/4 section corner at intersection with the E - W center line of section 21.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground and in a collar of stone, with aluminum cap marked:

T11N R18W  
C 1/4 S21  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a SW slope in sagebrush.

**78.890** The 1/4 section corner of sections 16 and 21.

From the 1/4 section corner of sections 21 and 22, monumented with an iron post 2 1/2 ins. diam., projecting 6 ins. above the ground, and in a collar of stone, with brass cap marked as described in the official record of the resurvey by C.P. Sylvester in 1979.

S. 89°14.2' W., on the E - W center line of section 21.

**37.742** The center 1/4 section corner of section 21.

**57.690** Point for the center W 1/16 section corner of section 21.

Set an aluminum post 30 ins. long 2 1/2 ins. diam. 24 ins. in the ground with aluminum cap marked:

T11N R18W  
C  $\frac{W\ 1/16}{S21}$  C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on nearly level land in cleared area with scattered juniper.

**77.638** The 1/4 section corner of sections 20 and 21.

From the W 1/16 section corner of sections 21 and 28.

N. 0°26.8' W., on the N - S center line of the SW 1/4 of section 21.

THE SUBDIVISION OF SECTION 21,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

39.456

The center W 1/16 section corner of section 21.

---

N. 0°26.8' W., on the N - S center line of the NW 1/4 of section 21.

39.866

The W 1/16 section corner of sections 16 and 21.

---

The Subdivision of Section 28,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 28 and 33.

N. 0°04.2' E., on the N - S center line of section 28.

20.267

Point for the center S 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C  
S 1/16 | S28  
C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently rolling land in sagebrush.

40.534

Point for the center 1/4 section corner, at intersection with the E - W center line of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gently, rolling SE slope in sagebrush.

80.924

The 1/4 section corner of sections 21 and 28.

---

THE SUBDIVISION OF SECTION 28,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

From the 1/4 section corner of sections 27 and 28.

S.  $88^{\circ}59.4'$  W., on the E - W center line of section 28.

**20.016** Point for the center E 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C —  $\frac{E \ 1/16}{S28}$  — C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a rolling SE slope in sagebrush.

**40.032** The center 1/4 section corner of section 28.

**59.832** Point for the center W 1/16 section corner of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C —  $\frac{W \ 1/16}{S28}$  — C  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on a gentle, W slope on top of low ridge, bears NE and SW, in sagebrush.

**79.632** The 1/4 section corner of sections 28 and 29.

---

From the E 1/16 section corner of sections 28 and 33.

N.  $0^{\circ}02.4'$  W., on the N - S center line of the SE 1/4 of section 28.

**40.796** The center E 1/16 section corner of section 28.

---

From the W 1/16 section corner of sections 28 and 33.

THE SUBDIVISION OF SECTION 28,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°29.2' E., on the N - S center line of the SW 1/4 of section 28.

20.138

Point for the SW 1/16 section corner of section 28, at intersection with the E - W center line of the SW 1/4 of section 28.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., ins. in the ground, with aluminum cap marked:

T11N R18W  
SW 1/16 S28  
1993

Set a steel fence post alongside the aluminum post.

The corner is located on gently, rolling land in sagebrush.

40.277

The center W 1/16 section corner of section 28.

---

From the center S 1/16 section corner of section 28.

S. 89°21.6' W., on the E - W center line of the SW 1/4 of section 28.

19.946

The SW 1/16 section corner of section 28.

39.892

The S 1/16 section corner of sections 28 and 29.

---

The Subdivision of Section 32,  
T. 11 N., R. 18 W., Salt Lake Meridian, Utah.

---

From the 1/4 section corner of sections 5 and 32, on the south boundary of the township, hereinbefore described.

N. 0°05.0' W., on the N - S center line of section 32.

39.968

Point for the center 1/4 section corner, at intersection with the E - W center line of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T11N R18W  
C 1/4 S32  
1993

Set a steel fence post alongside the aluminum post.



THE SUBDIVISION OF SECTION 32,  
T. 11 N., R. 18 W., SALT LAKE MERIDIAN, UTAH

## CHAINS

The corner is located on gently rolling land in sagebrush.

**79.936** The 1/4 section corner of sections 29 and 32.

---

From the point for the 1/4 section corner of sections 32 and 33.

S. 89°43.8' W., on the E - W center line of section 32.

**20.131** Point for the center E 1/16 section corner of section 32.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

$$\begin{array}{c} \text{T11N R18W} \\ \text{C} \text{ --- } \text{E } 1/16 \text{ --- } \text{C} \\ \text{S32} \\ \text{1993} \end{array}$$

Set a steel fence post alongside the aluminum post.

**40.262** The center 1/4 section corner of section 32.

**80.524** The 1/4 section corner of sections 31 and 32.

---

From the E 1/16 section corner of sections 5 and 32, on the south boundary of the township, hereinbefore described.

N. 0°05.3' W., on the N - S center line of the SE 1/4 of section 32.

**39.993** The center E 1/16 section corner of section 32.

---

N. 0°05.3' W., on the N - S center line of the NE 1/4 of section 32.

**39.993** The E 1/16 section corner of sections 29 and 32.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Todd S. Snyder	Surveying Aid


## CERTIFICATE OF SURVEY

I, *Gail E. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *12th day of May, 1993*, I have *dependently resurveyed portions of the north, west (Guide Meridian) and south boundaries, and a portion of the subdivisional lines, and subdivided sections 3, 6, 7, 10, 15, 18, 21, 28, and 32, in Township 11 North, Range 18 West,*

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 22, 1997

Date

  
(Cadastral Surveyor)

\_\_\_\_\_  
Date

\_\_\_\_\_  
(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of portions of the north, west (Guide Meridian) and south boundaries, and a portion of the subdivisional lines and the subdivision of sections 3, 6, 7, 10, 15, 18, 21, 28, and 32, Township 11 North, Range 18 West, Salt Lake Meridian, Utah,*

executed by *Gail E. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

April 24, 1997

Date



(Chief Cadastral Surveyor for Utah)